

RG59 D112 COAXIAL CABLE

APPLICATION


❖ High quality RG Type Coaxial cable,75 Ohm suitable for many applications, particularly broadcast and CCTV installations.

PRODUCT FACTS

- ❖ INDOOR USE, Accepts 300m longer
- Suitable for shop-lot, home, factory

PRODUCT CODE

❖ RG59-ALL-D112-300M



TECHNICAL DATA

ITEM		UNIT	SPEC. VALUE
Inner Conductor	Material		Bare Copper
	Dia.(approx)	mm	0.65 ± 0.15
Insulation	Material		Solid PE
	Nom. Thickness	mm	1.56 ± 0.18
	Dia.(approx)	mm	3.70 ± 0.18
	Colour		Natural
Outer Conductor	Type		Braid
	Material		Bare Copper
	Coverage	%	95 ± 3
	Dia.(approx)	mm	0.08 x 112
Jacket	Material		PVC
	Nom. Thickness	mm	0.80 ± 0.2
	Colour		Black
	Dia.(approx)	mm	5.90 ± 0.20
CHARACTERISTICS			
DC Conductor Resistance at 20°C			$< 26.1\Omega/100m$
Insulation Resistance at 20°C			> 200 MΩ.m
Nominal Velocity of Propagation			$66.6 \pm 3\%$
Capacitance			$67 \pm 5 \text{ pF/m}$
Characteristic Impedance at 20°C,200MHz			$75 \pm 5\Omega$
PACKING			WEIGHT
Wooden drum - 300x300x200(mm)	300m/drum		14.8kg