

Bolting

CP6120 PASED

1-1/2"



**THE BEST SUPER INDUSTRIAL
1-1/2": COMPACT,
COMFORTABLE & EXTREMELY DURABLE**

FEATURES

- Super Industrial 1-1/2" impact wrench
- Reliable 2-jaw clutch with the highest Blows per Minute
- Full Teasing (inside) trigger with durable reverse
- Durable aluminum body & indestructible steel clutch housing
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- 360° adjustable D-type side handle

BENEFITS

- Best 1-1/2" impact to loosen very big bolts quickly and smoothly
- Operator comfort and control thanks to great ergonomics even at VERY high torque
- "Never ending" torque due to the 2-Jaw clutch
- Unmatched durability with Reliable mechanism & durable housing
- Excellent for very demanding industries such as Heavy Industrial Maintenance & Production applications



CP6120 PASED

CP6120 GASED

Same features as CP6120 PASED with outside trigger

CP6120 PASEL or GASEL

Same features as
CP6120 PASED or GASED
with #5 Spline Drive

#5



Benefits : avoid loss of torque,
reduce vibrations, increase durability of anvil.

CP6930-D35

1-1/2"



1-1/2" IMPACT FOR INDUSTRIAL MAINTENANCE

FEATURES

- 1-1/2" industrial impact wrench with hole type socket retainer
- Durable twin hammer clutch with oil bath
- Durable aluminum body & clutch housing
- Reversible D-type side handle
- Double stage internal trigger
- 3-settings power regulator
- Adjustable exhaust

BENEFITS

- Robust Double Dog clutch with oil bath
- Durable aluminum housing with steel trigger and protective plate in the front
- Operator comfort and control with 3-positions regulator and side D-handle



CP6120 PASED

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @ LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
					ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K			
CP6120 GASED	T018237	1-1/2"	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 GASEL	T017755	#5	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 PASED	T018841	1-1/2"	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 PASEL	T018235	#5	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6930-D35	615 159 0390	1-1/2"	850	4,300	445-1,950	600-2,650	2,875	3,900	31.6	14.4	17.3	440	64.0	30.0	16.1	7.2	100	111	1/2

All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

1-1/2" & 2-1/2" Impact Wrenches

CP0614 PALED

1-1/2"



CP0614 GALED

Same features as CP0614 PALED with outside trigger

EXTREME POWER & LIGHT WEIGHT IN 1-1/2"

FEATURES

- 1-1/2" industrial impact wrench
- Reliable 2-jaw clutch
- Body & clutch aluminum housing
- Bar type side handle
- Steel inside trigger
- Hole type socket retainer with O-ring

BENEFITS

- Designed for Industrial Maintenance & Production
- Heavy performance with 2-jaw mechanism
- Operator comfort with light weight
- Easy control even at high torque levels
- Reliable impact mechanism
- 3-part construction & easy to maintain

CP6130-T70

1-1/2"



POWERFUL, DURABLE & SMOOTH 1-1/2" T-HANDLE

FEATURES

- 1-1/2" Super Duty T-Handle
- Reliable Double Rocking Dog clutch
- Durable aluminum body & clutch housing
- 5-positions regulator, progressive trigger & Easy reverse
- Adjustable side handles and 2 vertical handles
- Suspension hole for easy hoist/balancer hooking

BENEFITS

- Incredible breaking torque for bolts up to M54
- Fast and smooth operations for Industrial Maintenance & Production applications
- Operator comfort and control due to wide handles positioning
- Reliable Double Rocking Dog mechanism & durable housing
- Compact 3-part construction for easy maintenance



CP6130-T70

CP6240-T120

2-1/2"



POWERFUL, DURABLE & SMOOTH 2-1/2" T-HANDLE

FEATURES

- 2-1/2" Super Duty T-Handle
- Reliable Double Rocking Dog clutch
- Durable aluminum body & clutch housing
- 5-positions regulator, progressive trigger & Easy reverse
- Adjustable side handles and 2 vertical handles
- Suspension hole for easy hoist/balancer hooking

BENEFITS

- Incredible breaking torque for bolts up to M75
- Fast and smooth operations for Industrial Maintenance & Production applications
- Operator comfort and control due to wide handles positioning
- Reliable Double Rocking Dog mechanism & durable housing
- Compact 3-part construction for easy maintenance



See accessories on pages 30 to 34

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
			bpm	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K	ISO 15744 - dB(A)	in.	
CP0614 GALED	T020021	1-1/2"	500	2,500	1,200-2,400	1,620-3,250	4,000	5,420	31.5	14.3	16.4	417	58.0	27.4	18.8	4.0	97	108	1/2
CP0614 PALED	T020022	1-1/2"	500	2,500	1,200-2,400	1,620-3,250	4,000	5,420	31.5	14.3	16.4	417	58.0	27.4	18.8	4.0	97	108	1/2
CP6130-T70	615 159 0010	1-1/2"	180	4,000	2,430-5,240	3,300-7,100	9,220	12,500	72.6	33.0	19.7	500	67.3	31.8	4.7	1.7	104	115	1
CP6240-T120	615 159 0020	2-1/2"	120	4,000	3,760-9,150	5,100-12,400	18,440	25,000	132.0	60.0	24.1	610	74.9	35.3	4.5	1.5	107	118	1

All models: Hose int. 1/2" (13mm) or 1" (25mm) - @90 PSI (@6.3 Bar) Listed specifications are for reference only. Please check documents in each tool or on www.cp.com