

Bolting

CP6060 SASAK

1"



THE MOST COMPACT & LIGHTWEIGHT INDUSTRIAL 1"

FEATURES

- Super Industrial lightweight 1" impact wrench
- Reliable 2-jaw clutch
- Aluminum body & steel clutch housing
- Durable reverse & steel trigger
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with O-Ring

BENEFITS

- Compact 1" to break big bolts on very demanding industries
- Operator comfort and control due to great ergonomics even at high torque levels
- "Never ending" torque thanks to the 2-Jaw clutch
- Unmatched durability with Reliable mechanism & durable housing
- Ideal for Industrial Maintenance & Production applications

CP6060 ZASAK

Same features as CP6060 SASAK with zinc housing for spark resistance



CP894

1"



SMOOTH OPERATION & ROBUSTNESS

FEATURES

- 1" pistol impact wrench with Dual retainer
- DYNA-PACT (Pin clutch) mechanism in oil bath
- One-handed reverse button with 3 settings of power
- Adjustable side handle

BENEFITS

- Ideal tool for General Maintenance operations
- Clutch delivers smooth operation and extended durability
- Side handle provides additional comfort and control

CP6910-P24

1"



POWERFUL, DURABLE & COMFORTABLE

FEATURES

- 1" Industrial Pistol impact wrench
- Oil Bath Pinless rocking dog clutch
- Durable Aluminum body & Rubber protective cover on clutch housing
- D-type side handle with Rubber grip
- Dual (hole & ring) type socket retainer
- Removable hole plate for suspension
- Metal trigger & reverse knob for longer durability
- 3-positions regulator & easy reverse

BENEFITS

- Ideal for a variety of heavy Industrial Maintenance applications
- Reliable & powerful oil bath Pinless Rocking Dog clutch
- Operator comfort with many ergonomic features
- 3-part construction reducing downtime maintenance



CP6910-P24



See accessories on pages 30 to 34

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
			bpm	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K	ISO 15744 - dB(A)	in.	
CP6060 SASAK	T024060	1"	1,000	3,500	195-650	265-880	1,000	1,356	11.9	5.4	7.6	194	42.0	19.8	14.2	4.1	95	106	3/8
CP6060 ZASAK	T024063	1"	1,000	3,500	195-650	265-880	1,000	1,356	11.9	5.4	7.6	194	42.0	19.8	14.2	4.1	95	106	3/8
CP6910-P24	615 159 0070	1"	650	5,000	370-1,550	500-2,100	1,920	2,600	22.5	10.2	11.4	290	40.2	19.0	8.9	2.5	97	108	1/2
CP894	T024743	1"	720	4,100	100-1,200	136-1,627	1,700	2,305	25.0	11.3	11.8	298	45.0	21.2	8.3	2.7	100	111	1/2

All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

1" Impact Wrenches

Bolting

CP0611P RLS

#5



THE BEST SUPER INDUSTRIAL WITH SPLINE #5

FEATURES

- Super industrial impact with spline #5
- Reliable 2-jaw clutch
- Aluminum body & steel clutch housing
- Protective & Durable reverse
- Compact 3-part construction & easy maintenance
- 360° adjustable D-type side handle

BENEFITS

- Best impact to target big bolts on very demanding industries thanks to Spline #5
- Spline #5: avoid loss of torque, reduce vibrations, increase durability of anvil
- Operator comfort and control thanks to perfect ergonomic design even at VERY high torque
- "Never ending" Torque due to the 2-Jaw clutch
- Unmatched durability with reliable mechanism & durable housing
- Excellent for Heavy Industrial Maintenance Production applications



CP0611PRS



See accessories on pages 30 to 34

CP0611P RS

1"



THE BEST SUPER INDUSTRIAL 1"

FEATURES

- Super Industrial 1" impact wrench
- Reliable 2-jaw clutch
- Aluminum body & steel clutch housing
- Protective & Durable reverse
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- 360° adjustable D-type side handle

BENEFITS

- Best 1" impact to targets tough bolts on very demanding industries
- Operator comfort and control thanks to great ergonomics even at VERY high torque
- "Never ending" torque due to the 2-Jaw clutch
- Unmatched durability with reliable mechanism & durable housing
- Excellent for Heavy Industrial Maintenance and Production applications



CP0611P RS


MODEL	PART NUMBER	DRIVE	BLOWS PER MIN		FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @ LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS. ISO 15744 - dB(A)	SOUND POWER	AIR INLET
			in.	bpm		rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a			
CP0611P RLS	T025414	#5	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	23.1	10.5	10.7	272	48.0	22.6	16.8	4.7	102	113	1/2	
CP0611P RS	T025413 or 615 159 0050	1"	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	23.1	10.5	10.7	272	48.0	22.6	16.8	4.7	102	113	1/2	

All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

Bolting

CP7780



LIGHTWEIGHT FOR GENERAL MAINTENANCE


FEATURES

- 1" D-Handle impact wrench with Dual retainer (Hole + Ring)
- Only 15 lbs (6,8 kg) thanks to an aluminum housing giving less fatigue to the operator
- Integrated protective cover on the clutch housing
- Twin hammer mechanism in oil bath for durability
- Double stage trigger and dedicated lever for forward & reverse
- Ergonomic side handle with soft touch grip
- 4-position power setting for both directions and on both sides of the tool

BENEFITS

- Maximize operator comfort with a lightweight impact
- Ergonomic and intuitive handling
- High Power to Weight ratio for General Maintenance applications

CP7782



HIGH TORQUE & COMFORT


FEATURES

- 1" D-handle impact wrench with dual retainer (Hole + Ring)
- Pinless closed reinforced rocking dog impact mechanism
- Ergonomic side handle
- Integrated protective cover on the clutch housing
- Full teasing trigger
- Regulator with integrated forward/reverse with 3-position power settings in both directions

BENEFITS

- Great power for General Maintenance applications
- High motor efficiency for savings
- Reinforced clutch mechanism

CP6920-D24



POWERFUL, DURABLE & COMFORTABLE

FEATURES

- 1" Industrial D-Handle impact wrench
- Oil Bath Pinless rocking dog clutch
- Durable Aluminum body & Rubber protective cover on clutch housing
- D-type side handle with Rubber grip
- Dual (hole & ring) type socket retainer
- Removable hole plate for suspension
- Metal trigger & reverse knob for longer durability
- 4-positions regulator & easy reverse

BENEFITS

- Ideal for a variety of heavy Industrial Maintenance applications
- Reliable & powerful oil bath Pinless Rocking Dog clutch
- Operator comfort with many ergonomic features
- 3-part construction for reducing downtime maintenance



CP6920-D24



See accessories on pages 30 to 34

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
					ft.	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K			
CP6920-D24	615 159 0080	1"	700	5,000	370-1,550	500-2,100	1,920	2,600	22.7	10.3	14.2	360	40.2	19.0	8.4	2.8	100	111	1/2
CP7780	894 107 7800	1"	790	5,000	260-1,220	350-1,650	1,550	2,100	15.0	6.8	13.2	335	49.8	23.4	15.5	5.9	94	105	1/2
CP7782	894 107 7820	1"	500	5,200	370-1475	500-2,000	1,920	2,600	22.2	10.1	14.7	370	40.7	19.2	7.8	1.8	100	111	1/2


All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

1" Impact Wrenches

Bolting

CP6110 PASED



CP6110 GASED

Same features as CP6110 PASED with outside trigger

COMPACT, ERGONOMIC & VERSATILE INDUSTRIAL 1"

FEATURES

- 1" heavy-duty impact wrench
- Reliable Twin lobe clutch
- Robust Aluminum body & steel clutch housing
- 360° adjustable D-type side handle
- Steel inside trigger
- Hole-type socket retainer

BENEFITS

- The best industrial 1" for VERY soft joints applications
- Operator comfort with adjustable side handle and smooth operations
- Reliable clutch & durable housing
- 3-part construction for easy maintenance
- Excellent in Industrial Maintenance & Production



CP0611 PASED



See accessories on pages 30 to 34

CP0611 PASED



THE "REFERENCE" IN 1": COMPACT, COMFORTABLE & EXTREMELY DURABLE

FEATURES

- Super Industrial 1" impact wrench
- Reliable 2-jaw clutch with the highest Blows per Minutes
- Full Teasing (inside) trigger with durable reverse
- Durable aluminum body & indestructible steel clutch housing
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- 360° adjustable D-type side handle

BENEFITS

- Best 1" impact to loosen big bolts on very demanding industries
- Operator comfort and control thanks to perfect ergonomic design even at VERY high torque
- "Never ending" torque thanks to the 2-Jaw clutch
- Unmatched durability with reliable mechanism & durable housing
- Ideal for Heavy Industrial Maintenance and Production applications



CP0611 PASED

CP0611 GASED

Same features as CP0611 PASED with outside trigger

CP0611 HAZED

Same features as CP0611 PASED with zinc housing for spark resistance



CP0611 PASEL or GASEL

Same features as CP0611 PASED or GASED with #5 Spline socket retainer.



Benefits : avoid loss of torque, reduce vibrations, increase durability of anvil

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)	SOUND PRESS.	SOUND POWER	AIR INLET	
					ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s					a
CP0611 GASED	T022580	1"	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	22.5	10.2	12.5	318	48.0	22.6	16.1	4.5	97	108	1/2
CP0611 GASEL	T022581	#5	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	22.5	10.2	12.5	318	48.0	22.6	16.1	4.5	97	108	1/2
CP0611 HAZED	T022582	1"	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	22.5	10.2	12.5	318	48.0	22.6	16.1	4.5	97	108	1/2
CP0611 PASED	T022578	1"	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	22.5	10.2	12.5	318	48.0	22.6	16.1	4.5	97	108	1/2
CP0611 PASEL	T022579	#5	1,020	3,500	900-1,800	1,220-2,440	2,800	3,790	22.5	10.2	12.5	318	48.0	22.6	16.1	4.5	97	108	1/2
CP6110 GASED	T024425	1"	960	3,500	375-1,250	510-1,695	1,900	2,575	21.5	9.8	13.0	330	53.0	25.0	18.1	5.9	93	104	1/2
CP6110 PASED	T025100	1"	960	3,500	375-1,250	510-1,695	1,900	2,575	21.5	9.8	13.0	330	53.0	25.0	18.1	5.9	93	104	1/2

All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com

Bolting

CP6120 PASED

1-1/2"



**THE BEST SUPER INDUSTRIAL
1-1/2": COMPACT,
COMFORTABLE & EXTREMELY DURABLE**

FEATURES

- Super Industrial 1-1/2" impact wrench
- Reliable 2-jaw clutch with the highest Blows per Minute
- Full Teasing (inside) trigger with durable reverse
- Durable aluminum body & indestructible steel clutch housing
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- 360° adjustable D-type side handle

BENEFITS

- Best 1-1/2" impact to loosen very big bolts quickly and smoothly
- Operator comfort and control thanks to great ergonomics even at VERY high torque
- "Never ending" torque due to the 2-Jaw clutch
- Unmatched durability with Reliable mechanism & durable housing
- Excellent for very demanding industries such as Heavy Industrial Maintenance & Production applications



CP6120 PASED

CP6120 GASED

Same features as CP6120 PASED with outside trigger

CP6120 PASEL or GASEL

Same features as
CP6120 PASED or GASED
with #5 Spline Drive

#5



Benefits : avoid loss of torque,
reduce vibrations, increase durability of anvil.

CP6930-D35

1-1/2"



1-1/2" IMPACT FOR INDUSTRIAL MAINTENANCE

FEATURES

- 1-1/2" industrial impact wrench with hole type socket retainer
- Durable twin hammer clutch with oil bath
- Durable aluminum body & clutch housing
- Reversible D-type side handle
- Double stage internal trigger
- 3-settings power regulator
- Adjustable exhaust

BENEFITS

- Robust Double Dog clutch with oil bath
- Durable aluminum housing with steel trigger and protective plate in the front
- Operator comfort and control with 3-positions regulator and side D-handle



CP6120 PASED

MODEL	PART NUMBER	DRIVE	BLOWS PER MIN	FREE SPEED	WORKING TORQUE (FW)		MAX TORQUE (REV)		NET WEIGHT		LENGTH		AIR CONS. @ LOAD		VIBRATION LEVEL ISO 28927 (m/s ²)		SOUND PRESS.	SOUND POWER	AIR INLET
					ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K			
CP6120 GASED	T018237	1-1/2"	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 GASEL	T017755	#5	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 PASED	T018841	1-1/2"	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6120 PASEL	T018235	#5	960	3,000	600-2,000	815-2,710	3,500	4,740	33.9	15.4	14.8	375	60.0	28.3	21	6.6	102	113	1/2
CP6930-D35	615 159 0390	1-1/2"	850	4,300	445-1,950	600-2,650	2,875	3,900	31.6	14.4	17.3	440	64.0	30.0	16.1	7.2	100	111	1/2

All models: Hose int. 1/2" (13mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool or on www.cp.com