

**7 Series DF817 | BT817 | miP7 | CSN7**



***Dual Factor Advanced Security***  
***built to withstand harsh environments***

**smartersecuritytoday**

BQT's miPass range of DESFire and Mifare 13.56Mhz readers are the ideal choice for High Security with Peace of Mind. BQT has the best readers for every application including single, dual and triple factor authentication.

# Learn More miPass 7 Series

The **miPASS 7 Series** range offers superior security and flexibility through its customisation and encryption options to suit all access control requirements, delivering unrivalled security from the reader to the card.

The 7 Series reader is designed for applications where a high-level of security is required by combining smart card identification with a personal identification number (PIN) for secure user authentication and verification.

Reader operation can be configured for 'Card only', 'PIN only', 'Card or PIN' or 'Card & PIN' at the access control panel and can output any PINPAD format for all access control systems. Optionally, the PIN can be stored in the memory chip of a miPASS card.

Designed with a simple installation in mind, it can be installed on flush surfaces and mounted on most international standard gang boxes with the addition of backing plates to meet these standards. The reader is a low-profile, extremely robust and engineered unit built to withstand the harshest of environments. It features a 12 button illuminated keypad, made of silicone that is completely waterproof.

Ideal for new site installations or security upgrades of existing systems using 'Swipe' or 'Prox' (125 KHz) card and reader technologies, it offers a cost effective enhancement to your current access control system.

Available in four different models, the miPASS 7 Series range caters for all security requirements large or small, whether your projects are price or functionality

## miPass 7 Series Models

### >> DF817 • DESFire Technology

The DF817 DESFire reader offers 3DES encryption between a DESFire card and reader, delivering the most secure card transaction process available. It can be configured with various output protocols and programmed with customised encryption keys unique to each customer.

### >> BT817 • Mifare Technology

The BT817 Mifare reader can be configured with various output protocols and programmed with customised encryption keys unique to each customer. Also upgradeable with further security enhancements when requirements increase.

### >> miP7 • SPEK Technology

The miP7 reader features miPASS SPEK (Secure Proximity Encryption Keys) for secure transmission between a miPASS card and the reader. A secure, cost effective solution or upgrade for any system. Available in Wiegand output protocol only.

### >> CSN7 • Card Serial Number

The CSN9 reader will read any Mifare Smart Card's unique serial number and is available in 32 or 34 bit outputs.

## miPASS 7 series Specifications

\* Note specifications may change on products amended or updated without notice

	DF817	BT817	miP7	CSN7
Sector or serial	Container/Sector	Sector	Sector	Serial
Card type	DESFire 13.56MHz ISO14443A	Mifare 13.56MHz ISO14443A	Mifare 13.56MHz ISO14443A	Mifare 13.56MHz ISO14443A
miPASS card options	ESFire 4KB (other sizes & KeyTag optional)	Mifare 1KB & 4KB (other sizes & KeyTag optional)	Mifare 1KB & 4KB (KeyTag optional)	Any Mifare card
Sector keys	- Customisable - Site specific	- Customisable - Site specific	miPASS Secure Proximity Encryption Keys (SPEK)	N/A
Tamper switch	Available on request	Available on request	N/A	N/A
Read & write	Yes	Yes	Yes	Read only
Encryption	- 3DES format from reader to card - AES 128/256 bit from reader to controller via RS485. (HSM unit required)	- Mifare standard format from reader to card (Crypto 1) - AES 128/256 bit from reader to controller via RS485. (HSM unit required)	Mifare standard format, utilising SPEK from reader to card (Crypto 1)	N/A
Output protocol	- Wiegand 26 – 199 bit - RS485 - Or custom configurations	- Wiegand 26 – 199 bit - RS485 - Or custom configurations	Wiegand 26 bit only	- Wiegand 32 or 34 bit - Custom bit length available
Power requirement	12Vdc			
Current consumption	200mA			
Card read range	20-40mm (0.8" - 1.6") (typically)			
Operating temperature	-25°C to +65°C (-13°F to +149°F)			
Relative humidity	90% max, operating non-condensing			
Reader dimensions	90mm (L) x 90mm (W) x 27mm (D) (3.54" x 3.54" x 1.06")			
Keypad	12 button - illuminated			
Status LED's	Green & Red			
Audible tone	Internal & external Buzzer control			
Colour finish	Charcoal			
Certifications	FCC, CE, C-Tick			
IP Rating	IP67 - Internal or external applications			
Warranty	5 years			

BQT offers a complete range of smart card access control solutions to suit all physical and IT security requirements, including highly secure biometric, data encryption and CCTV technologies. **For futher information, please visit our website [www.bqtsolutions.com](http://www.bqtsolutions.com) or contact us at one of our global locations.**

#### AUSTRALIA & PACIFIC

BQT Solutions (Australia) Pty. Limited  
Level 1, 82 Waterloo Road  
Macquarie Park, NSW 2113 Australia  
Phone: +61 (0)2 8817 2800  
Fax: +61 (0)2 8817 2811  
Email: [sales@bqtsolutions.com](mailto:sales@bqtsolutions.com)

#### EUROPE AND MIDDLE EAST

BQT Solutions (UK) Limited  
Regal House, 70 London Road Twickenham  
Middlesex, TW1 3QS United Kingdom  
Phone: +44 (0)20 8622 4428  
Fax: +44 (0)20 8622 4401  
Email: [sales@bqtsolutions.co.uk](mailto:sales@bqtsolutions.co.uk)

#### GREATER ASIA

BQT Solutions Singapore Office  
Mediapolis, 71 Ayer Rajah Crescent, #03-03  
Singapore 139951  
Phone: +65 6220 7970  
Fax: +65 6220 7656  
Email: [salesasia@bqtsolutions.com](mailto:salesasia@bqtsolutions.com)