


# Flushing & Pipe Cleaning

## Pipe Cleaning Electric



Model  230 V 110/115 V

R 550 including guide hose 16.0 **72686** **72631**

Tool sets and accessories starting on  238

### R 550

#### Drain cleaning machine for pipe Ø 20 - 100 mm

Reliable, high-performance drain cleaning machine with a variety of general purpose maintenance uses

#### Product Profile

##### APPLICATION AREA

##### Especially light, compact and handy design:

Ideal for the universal service use by pipe obstructions in connecting pipes from wash basins, toilets, sewage pipes, floor drains and roof drainage

##### KEY FEATURES

- Extremely light
- Direct attachment of 16 mm spirals
- Optional Ø 8 and 10 mm with adaptor magazine possible
- Maximum working length 40 m, with Ø 16 mm S-spiral

##### TECHNICAL DATA


<b>For pipe diameters:</b>	Ø 20 - 100 mm
<b>Direct attachment:</b>	Ø 16 mm spirals
<b>With adaptor magazine:</b>	Ø 8 mm and 10 mm
<b>Max. working length:</b>	40 m with Ø 16 mm S-spirals 10 m with Ø 8 and 10 mm spirals
<b>Rating:</b>	440 W (Power input)
<b>Voltage:</b>	230 / 110 / 115 V, 50 Hz
<b>Speed:</b>	583 min <sup>-1</sup> , RH and LH drive
<b>Weight:</b>	16.0 kg

11



Model  230 V 110/115 V

R 600 including guide hose 20.9 **72687** **72632**

Tool sets and accessories starting on  238

### R 600

#### Drain cleaning machine for pipe Ø 20 - 150 mm

For installation and maintenance work in hospitals and municipal facilities

#### Product Profile

##### APPLICATION AREA

##### Universal use both indoors and outdoors:

The powerful motor works reliably even against stubborn obstructions. A wide range of accessories is available

##### KEY FEATURES

- Direct up take from 16 mm and 22 mm spirals
- Optional Ø 8 and 10 mm with adaptor magazine possible
- Maximum working length 50 m, with Ø 16 mm S-spirals
- Maximum working length 60 m, with Ø 22 mm S-spirals

##### TECHNICAL DATA

<b>For pipe diameters:</b>	Ø 20 - 150 mm
<b>With direct attachment:</b>	Ø 22 and 16 mm spirals
<b>With adaptor magazine:</b>	Ø 8 und 10 mm
<b>Max. working length:</b>	60 m with Ø 22 mm S-spirals 50 m with Ø 16 mm S-spirals 10 m with Ø 8 and 10 mm spirals
<b>Rating:</b>	690 W (Power input)
<b>Voltage:</b>	230 / 110 / 115 V, 50 Hz
<b>Speed:</b>	467 min <sup>-1</sup> , RH and LH drive
<b>Weight:</b>	20.9 kg

# Flushing & Pipe Cleaning

## Pipe Cleaning Electric

### R 650

#### Drain cleaning machine for pipe Ø 20 - 150 mm

For professional mobile drain cleaning. Compact, robust and powerful, even by the toughest pipe obstructions

#### Product Profile

##### APPLICATION AREA

**Perfectly suited for rough use and in extreme working conditions:** Quiet operation and powerful cleaning action, even when cutting through roots or grinding out cement and lime deposits

##### KEY FEATURES

- Double motor performance (cp. R 600)\*
- Flexible with drive lever that can be fitted on the side
- Direct up take of 22 mm and 16 mm spirals
- Optional Ø 8 and 10 mm with adaptor magazine possible
- Maximum working length 65 m, with Ø 22 mm S-spiral



##### TECHNICAL DATA

<b>For pipe diameters:</b>	Ø 20 - 150 mm
<b>Direct attachment:</b>	Ø 22 und 16 mm spirals
<b>With adaptor magazine:</b>	Ø 8 mm and 10 mm
<b>Max. working length:</b>	65 m with Ø 22 mm S-spirals 55 m with Ø 16 mm S-spirals 10 m with Ø 8 and 10 mm spirals
<b>Rating:</b>	1,350 W (Power input)
<b>Voltage:</b>	230 / 110 / 115 V, 50 Hz
<b>Speed:</b>	623 min <sup>-1</sup> , RH and LH drive
<b>Weight:</b>	22.8 kg



Drive lever can be fitted on the side

Flexible use

Model		230 V	110/115 V
R 650 including guide hose	22.8	<b>72688</b>	<b>72633</b>
Tool sets and accessories starting on  238			

### R 750

#### Drain cleaning machine for pipe Ø 20 - 200 mm

For professional mobile drain cleaning. Compact, robust and powerful, even by the toughest pipe obstructions

#### Product Profile

##### APPLICATION AREA

**Perfectly suited for the cleaning of domestic connections and main pipes:**

Quiet operation and powerful cleaning action. Usable for such as chain spinning, grinding and cutting roots

##### KEY FEATURES

- Drive lever can be rotated (180°), locked and used as a handle for easy wheeling
- Direct up take of 32 mm and 22 mm
- Optional Ø 16 mm with clutch jaw possible
- Maximum working length 70 m, with Ø 22 mm S-spirals



##### TECHNICAL DATA

<b>For pipe diameters:</b>	Ø 20 - 200 mm
<b>With direct attachment:</b>	Ø 32 and 22 mm spirals
<b>With clutch jaw:</b>	Ø 16 mm
<b>Max. working length:</b>	80 m with Ø 32 mm S-spirals 70 m with Ø 22 mm S-spirals 55 m with Ø 16 mm S-spirals
<b>Rating:</b>	1,400 W (Power input)
<b>Voltage:</b>	230 / 110 / 115 V, 50 Hz
<b>Speed:</b>	467 min <sup>-1</sup> , RH and LH drive
<b>Weight:</b>	33.5 kg



Full rubber transport wheels

Comfortable transport, high mobility and a secure stand

Model		230 V	110/115 V
R 750 including guide hose	33.5	<b>72689</b>	<b>72634</b>
Tool sets and accessories starting on  238			

11