



AT-4000 Series

Attenuators



AT-4000 Series Attenuators

Design with ergonomics for the human hand in mind, AT-4000 Series Attenuators' control knob comes in a size that provides comfortable grip and excellent control with every turn. Consisting of 8-step attenuation, the series is built to provide precision volume control with a difference of 3 dB in every step. The built-in overriding relay feature allows emergency paging which is indicated by the LED light when activated.

AT-4000 Series Attenuators come in 5 different ratings - 12 W, 30 W, 60 W, 120 W, and 200 W.

Features

- 8-step attenuation level control (+/-3 dB)
- Ergonomic control knob with better grip for easy turn
- 24 VDC overriding relay with red LED indicator
- Terminal block for thicker diameter cable
- Clip-on face plate
- 2- / 3- / 4-wire system
- Surface or flush mount
- Glossy finish in white



Specifications

Attenuator	AT-4012	AT-4030	AT-4060	AT-4120	AT-4200
Input Capacity	12 W	30 W	60 W	120 W	200 W
Attenuation	8 steps (0 dB, -3 dB, 6 dB, 9 dB, 12 dB, 15 dB, 18 dB, OFF)				
Override Indicator	Red LED (4-wire connection only)				
Overriding Voltage	24 V, 11 mA DC (4-wire connection only)				
Terminal	Screw-type x 5				
Usable Cable	Cable range 22 - 14 AWG				
Finish	Knob, Cover Panel: ABS Resin, White (RAL9016 or equivalent) Front Panel (plate): Surface treated steel plate				
Dimensions	86 (W) x 86 (H) x 24 (D) mm	86 (W) x 86 (H) x 51 (D) mm			
Weight	120 g	450 g	460 g	480 g	490 g
Accessories	- Black box (85.5 (W) x 86 (H) x 51 (D) mm) x 1, Plate mounting screw x 2				