

**PRODUCT SPECIFICATION**

Page :1

Revised edition no : 01

P-714 10W-30 SJ/CF MOTOR OIL

Effective Date: 15-7-2014

Description:

Highly refined motor oil which contains advance additive which provide maximum protection for the gasoline engine. It has extremely anti-oxidation and thermal stability properties meet the requirement of API SJ/CF.

Recommended for diesel and gasoline engine operating under extreme service conditions and engine that are equipped with high pressure turbocharged.

Product Specification : 10W-30 SJ/CF

<u>Test</u>	<u>Unit</u>	<u>Typical Results</u>
Density @ 15 Deg C (ASTM-D4052)	KG/L	0.882
Viscosity @ 100 Deg C @ 40 Deg C (ASTM-D445)	cst cst	10.85 72.2
Viscosity Index (ASTM-D2270)	-	140.3
Flash Point COC (ASTM-D92)	Deg C	218.2
Pour Point (ASTM-D92)	Deg C	-29.0

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com