

**PRODUCT SPECIFICATION**

Page :1

Revised edition no : 01

**P-713 HD 30 MOTOR OIL**

Effective Date: 15-7-2014

**Description:**

A high quality crankcase lubricant which has good anti-oxidation and anti-wear characteristic for diesel and gasoline engine operated in mild to moderate duty.

**Product Specification : HD 30 Motor Oil**

<b><u>Test</u></b>	<b><u>Unit</u></b>	<b><u>Typical Results</u></b>
Density @ 15 Deg C (ASTM-D4052)	KG/L	0.89
Viscosity @ 100 Deg C @ 40 Deg C (ASTM-D445)	cst cst	10.8 94.6
Viscosity Index (ASTM-D2270)	-	98
Flash Point COC (ASTM-D92)	Deg C	258

**Note**

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

---

**TLC-KOYA CHEMICALS MANUFACTURING SDN BHD**

No.22 &amp; 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: [www.koyachemicals.com](http://www.koyachemicals.com) EMAIL: [admin@koyachemicals.com](mailto:admin@koyachemicals.com)