



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 00
P-608 HYDRAULIC OIL AW 68	Effective Date: 1-3-2014

Description:

A multi-purpose and sulphur-phosphorous sourced lubricating oils distinguished by its high oxidation resistance, anti-stick-slip properties and excellent rust-protection and corrosion protection meet AW 68.

PRODUCT SPECIFICATIONS: AW 68

<u>TEST</u>	<u>UNIT</u>	<u>TYPICAL RESULTS</u>
Density @ 15 Deg C	Kg/1	0.870
Viscosity @ 100 Deg C	cst	67-80
@ 40 Deg C (ASTM-D445)	cst	-
Viscosity Index (ASTM-D2270)	-	102
Flash Point COC (ASTM-D92)	Deg C	220
Pour Point (ASTM-97)	Deg C	-12

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com