



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 01
P-604 2 STROKE ENGINE OIL	Effective Date: 10-7-2014

(AUTOMATIVE LUBRICANT) (GASOLINE ENGINE OIL)

Product Description

An environment friendly 2-cycle engine oil specially formulated with synthetic components to reduce the visible exhaust smoke. The oil greatly reduces spark plug fouling and maintains engine power by controlling deposits. It also protects the engine from wear and corrosion. It reduces the exhaust emission and thus help to reduce air pollution. Meets the requirements of API TC and Kawasaki KH 125 piston seizure and cleanness test.

Features

- Good detergency and dispersancy to inhibit carbon deposit, maintaining engine machine parts cleanliness.
- A low - ash formula, low exhaust smoke level, maintaining spark plug cleanliness.
- Prevents pre-ignition caused by deposits in combustion chamber.

Application

- Suitable for air - cooled two - stroke motorcycle engines.
- Mixing ratio: refer to engine manufacturer's recommendation.

Typical properties

Viscosity @ 100°C , cSf		: 6.5
Flash Point (COC), °C	min	: 70
Sediment,%	max	: 0.01
Sulfate Ash, wt%	max	: 0.25

Packing

500ml, 1000ml, 5Litres, 200Litres

Storage

The shelf life for P-604 in unopened and undamaged packing is 24 months in far eastern conditions, when possible. Store the product in dry conditions and protect from contact with any water and direct sunlight. Do not freeze.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com