



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 01
P-606 CHASSIS GREASE	Effective Date: 10-7-2014

Description:

P-606 Chassis Grease is calcium based good quality grease providing maximum lubrication for a broad range of application. It has steady working temperature range up to 100°C / 220°F.

Precaution

It resists water wash out, provides good mechanical stability and reduced friction and wear. Avoid contact with skin. Do not ingest of this should occur, drink large volumes of water and seek medical attention.

Keep out of reach of children.

Physical and Chemical Properties

Physical state	:	Semi solid at ambient temperature
Colour	:	Deep Green
Odour	:	Characteristic mineral oil
Density at 15°C (Kg/M3)	:	800
Solubility in water	:	Negligible
Stability	:	Stable

Storage

Keep container sealed when not in use.

Keep away from direct sunlight.

Packing

4Kgs, 15Kgs, and 180Kgs.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com