



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 01
P-5508 WOOD WORKING GLUE	Effective Date: 10-7-2014

Description:

P-5508 Wood working glue is a ready to use polyvinyl alcohol based glue. Non toxic, non flammable, fast and easy setting for gap filling. It is non-staining and dry clear, professionals and handymen use for timber and furniture jointing, can also be used in schools and hobby applications.

Physical Properties

Appearance	:	Milky compound
Colour	:	Paper white (Clear when dry)
Viscosity	:	15,000cps + 1000cps
Stability	:	One year, under normal storage
Flash Point	:	None
Solubility	:	Indefinite in water
Solid content	:	Approx 40%

Features

Biodegradable	-	hence safe to the environment.
Safe	-	non toxic, non flammable safe for hand and skin.
Easy to use	-	easy setting

Precaution

Keep away from eyes, if contact with eyes, flush with plenty of water and obtain medical advice.
Keep out of reach of children.

Storage

Store in cool and dry place, keep away from direct ultra violet sunlight. Keep container tightly closed. As a general precaution, it should be used within six to twelve months of delivery.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com