

**MATERIAL SAFETY DATA SHEET**

Page :1

Revised edition no : 00

P-132 BRAKE FLUID DOT 3

Effective Date: 18-6-2014

1 Identification of the Product and the company

Chemical Name : Brake Fluid Dot 3
Type of product chemical family : Lather Dressing
Use : Degreasing Solution
Producer : TLC-KOYA CHEMICALS MANUFACTURING SDN BHD
No.22 & 23, Jalan Maju 1,
Cemerlang Industrial Estate,
81800 Ulu Tiram, Johor, Malaysia.
Tel: 607-8675798 Fax: 607-8675799
Website: www.koyachemicals.com Email: admin@koyachemicals.com

Emergency phone nr : See producer

2 Hazard Identification

Health hazardous : Harmful if swallowed. Irritating to skin. Risk of serious damage to eyes.
Harmful: danger of serious damage to health, by prolonged exposure and if swallowed.

3 Composition / Information on Ingredients

Hazardous ingredients : 2.2 Dihydroxydiethyl ether
Monoethylene glycol
Triethylene glycol
Anti-oxidant
Corrosion inhibitor
Amine

4 First Aid Measures

Inhalation : Remove patient to a clean atmosphere and administer oxygen if it is necessary. Consult a physician immediately.

Skin Contact : Flush exposed area with cool water. If irritation persists consult a physician immediately.

Eye Contact : Flush with cool running water, if irritation developed consult a Physician immediately.

Ingestion : Do not induce vomiting. Have patient drink large amounts of water or milk. Consult a physician immediately.

5 Fire-Fighting Measures

Flash Point (Tag Closed Tester) : 220°C
Extinguishing Media : Sand or Clay

Special Fire Fighting Procedures : Self-contained breathing apparatus are recommended for fire fighters.
Unusual Fire and Explosion Hazards : Not known

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



MATERIAL SAFETY DATA SHEET

Page :2

Revised edition no : 01

P-132 BRAKE FLUID DOT 3

Effective Date: 18-6-2014

6 Accidental Release measures

- Personal protection : - Wear PVC-gloves and goggles to contain spillage.
Avoid repeated skin contact.
- Environment precautions : - Prevent the product contaminating soil and groundwater. Prevent the product entering sewers and waterways.
Cfr.Section 12.
- Cleaning / recovery : - Large spillages : contain and pump into containers
- Small spillages : absorb on sand, earth...and collect into containers for disposal. Disposal should always comply with local, national or EEC regulations. Cfr.Section 13.

7 Handling and Storage

- Handling : Good industrial and personal hygiene practice should be followed. No eating and drinking in the workplace. Ensure adequate ventilation.
- Storage : Storage temperature : between +5 and +40°C.
Protect from frost and direct sunlight.
Drums and bottles : material is plastic or steel.
Bulk tanks : stainless steel, plastic coated materials... Clean bulk tanks periodically to prevent accumulation of bacteria.
- Specific use : Use the best available methods of handling our Products whereby the employees enjoy maximum safety and whereby the environment is minimally affected.

8 Exposure controls / personal protection

- Exposure limit values : No danger in normal ambient conditions.
There are no specific limiting values for professional exposure.
There are no biological limiting values.
User should determine the conditions for safe use of the product. Cfr. Section 7 "Handling and Storage".
- Exposure controls:
- Occupational exposure controls : Respiratory protection : not applicable
Hand protection : waterproof PVC-gloves (CE)
Eye protection : goggles or safety glasses (CE)
Skin protection : N/A
Avoid repeated skin contact.
- Environmental exposure controls : The product must not be discharge directly into drains or waterways without treatment.

9 Physical and chemical properties

- Boiling Point (°F) : Minimum 180°C (356°F)
- Vapor Pressure (mm hg) : N/A
- PH of concentrate : 6.5 +/- 0.5
- Appearance : Colourless or Red
- Specific Gravity (H₂O=1) : 1.12
- Percent Volatile by weight : N/A
- Evaporation Rate (Water=1) : N/A
- Viscosity at 40°C (cSt) : 13
- Dry Boiling Point : 260°C (500°F)
- Vapor Density (Air=1) : >1

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com



MATERIAL SAFETY DATA SHEET

Page :3

Revised edition no : 01

P-132 BRAKE FLUID DOT 3

Effective Date: 18-6-2014

10 Stability and reactivity

Stability	: Stable (Keep container tightly closed)
Condition to avoid	: N/D
Incompatibility (materials to avoid)	: Strong oxidizing and reducing agent & degreasing agent.
Hazardous Decomposition Products	: Carbon monoxide and carbon dioxide on combustion.
Hazardous Polymerization	: Will not occur.

11 Toxicological information

On product	: Low toxicity is indicated by available data. Under normal industrial conditions, there is no indication that the Product can be considered as a health risk. Skin contact should be avoided to prevent possible long-term or short-term sensitization.
------------	--

12 Ecological information

Ecotoxicity	: The Product is soluble with water and oil and as such could cover considerable distances if spilled into waterways. Even a small spillage will whiten the appearance of water. Water for sewage treatment, that has been contaminated. with small quantities of the Product, will not affect the biomass. High concentrations may be harmful to fish and micro organisms.
Mobility	: Not established.
Persistence and degradability	: There is only a slow environmental degradation of the Product.
Bioaccumulative potential	: There is seemingly no tendency for bioaccumulation.
Other adverse effects	: Unknown

13 Disposal Considerations

- The following advice only applies to the product as supplied
- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationship between living things, plants and their environment.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com

**MATERIAL SAFETY DATA SHEET**

Page :4

Revised edition no : 01

P-132 BRAKE FLUID DOT 3

Effective Date: 18-6-2014

14 Transport information

General information : This Product is not regulated for road/rail & sea transport.

15 Regulatory Information

Classification and labeling : Classification /symbol - not regulated
Governing directive : Occupational Safety and Health (Classification, Packaging and Labeling of Hazardous Chemicals) Regulations 1997
Safety advice : (May contain information in excess of requirements under applicable laws.
S23 Do not breathe gas/fumes/vapor/spray
S24 Avoid contact with skin
S33 Take precautionary measures against static discharges
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

16 Other information

Further information : None
Print date : 18-6-2014

N/A - Not Applicable N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such recommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com