PRODUCT SPECIFICATION

Page :1



P-560 ALMONO PROTECTANT

Revised edition no : 01

## Effective Date: 1-7-2014

# **Description:**

P-560 "Almono" Protectant is a solvent free low molecular protectnat weight silicone modified silicone for the preparation of product and shines plastic, vinyl, rubber, acrylic, fiberglass, finished leather, sealed wood furnitire.

Specification	
Appearance	: Milky Solution
Colour	: Milky white
Flash Point	: None
PH Value	: 0.4 - 0.5

## **Direction for Use**

1. Surface must be clean and dry.

2. Spray directly on surface and use a clean cloth spreas evenly, for best results, three applications are recommended. Let penetrate for 20 minutes after the first and second coat. Wide off the excess at last coat.

### **Precaution**

Not for use on glass, floor, paint, fabric or woven materials. Do not use on vehicle controls steering wheel, brake drums, car bench seat, cycle seats, cycle tires, handle grips and other surface were slipperiness may be hazardous. Avoid contact with eyes, keep out of reach of children.

### Storage

Store in dry place and away from direct sunlight.

## Packing 14 1

300ml

## Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.