# MATERIAL SAFETY DATA SHEET P-611 HIGH TEMPERATURE BEARING GREASE(LITHIUM MP)

Page :1 Revised edition no : 01

Effective Date: 12-7-2014

# 1 Identification of the Product and the company

	Chemical Name Type of product chemical family Use Producer	<ul> <li>High Temperature Bearing Grease (Lithium MP)</li> <li>Petroleum Grease</li> <li>Iubrication</li> <li>TLC-KOYA CHEMICALS MANUFACTURING SDN BHD No.22 &amp; 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia. Tel: 607-8675798 Fax: 607-8675799</li> <li>Website: www.koyachemicals.com Email: admin@koyachemicals.com</li> </ul>	
	Emergency phone nr	: See producer	
2	Hazard Identification		
	Health hazardous	: N/A	
3	Composition / Information on Ingredients		
	Hazardous ingredients Active Ingredients	: N/A : N/A	
4	First Aid Measures		
	Inhalation	: Remove person to fresh air and seek medical advice. If not breathing, apply artificial respiration and seek urgent medical aid.	
	Skin Contact	: Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. High pressure injection through the skin requires urgent medical attention fo rpossible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns (Do not remove material).	
	Eye Contact	: Wash with copious amounts of water for 15 minutes and seek medical advice if irritation develops or persists.	
	Ingestion	: If a large quantity is ingested seek medical attention. It may be necessary to induce vomiting, taking extreme care that the person foes not aspirate into the lungs. If aspiration occurs, urgent medical attention should be sought.	
	First Aid facilities	: Eye wash fountains and safety showers are recommended.	
5	Fire-Fighting Measures		
	Fire Hazard	: Not flammable under conditions of use. Is a combustible solid that will burn if preheated.	
	Sources of ignition advice Hazchem code	: Not applicable : Not applicable	



# MATERIAL SAFETY DATA SHEET P-611 HIGH TEMPERATURE BEARING GREASE(LITHIUM MP)

Page :2 Revised edition no : 01

Effective Date: 12-7-2014

#### 6 Accidental Release measures

Personal protection	<ul> <li>Wear PVC-gloves and goggles to contain spillage.</li> <li>Avoid repeated skin contact.</li> </ul>
Environment precautions	<ul> <li>Prevent the product contaminating soil and groundwater. Prevent the product enetring sewers and waterways.</li> <li>Cfr.Section 12.</li> </ul>
Cleaning / recovery	<ul> <li>Large spillages : contain and pump into containers</li> <li>Small spillages : absorb on sand, earthand collect into containers for disposal. Disposal should always comply with local, national or EEC regulations. Cfr.Section 13.</li> </ul>
7 Handling and Storage	
Handling	: Good industrial and personal hygiene practice should be followed. No eating and drinking in the workplace. Ensure adequate ventilation.
Storage	: Storage temperature : between +5 and +40°C.
	Protect from frost and direct sunlight. Drums and bottles : material is steel.
Specific use	: Use the best available methods of handling our Products whereby the employees enjoy maximum safety and whereby the environment is minimally affected.

# 8 Exposure controls / personal protection

Hazards of use/storage	; This product is combustible if preheated.
List of Dangerous Decompositior	n or Combustion Products
	: Combustion produces oxides of carbon, nitrogen, phosporus and zinc.
Fire-fighting products	; Keep storage tanks, pipelines, containers, fire exposed surfaces, etccool with water spray.
Type of extinguisher/	: Use foam, carbon dioxide or dry chemical. Do not use waer jets.
Fire fighting agents	
Precaution	: Water nar xause splattering or boil-over.
Protective clothing	: Self-contained breathing appratus is recommended during a fire.
Reactivity	: May react with strong oxidising agents.

### 9 Physical and chemical properties

NLGI grade	: 3
Colour	: Brown
Structure	: Extremely smooth
Soap Type	: Lithium MP
Penetration at 25 Degree C	: 220 to 250
Short term exposure, Degree C	: 180
Usable Temperature, Degree C	: 160



# MATERIAL SAFETY DATA SHEETPage :3P-611 HIGH TEMPERATURERevised edition no : 01BEARING GREASE(LITHIUM MP)Effective Date: 12-7-2014

10 Stabiity and reactivity	
Conditions to avoid	: Stable under the recommended storage conditions. Cfr. Section 7 "Storage". Bacterial degradation can occur if the Product is stored for an unuasually long period or is stored under unsuitable conditions.
Materials to avoid Hazardous decomposition products	: N/D : N/D
11 Toxicological information	
On product	<ul> <li>Low toxicity is indicated by available data.</li> <li>Under normal industrial conditions, there is no indication that the Product can be considered as a health risk.</li> <li>Skin contact should be avoided to prevent possible long-term or short-term sensitation.</li> </ul>
12 Ecological information	
Ecotoxicity	: The Product is soluble with water and as such could cover considerable distances if spilled into waterways. Even a small spillage will whiten the appearance of water. Water for sewage treatment, that has been contaminated. with small quantities of the Product, will not affect the biomass. High
Mobility Persistence and degradability Bioaccumulative potential Other adverse effects	concentrations may be harmful to fish and micro organisms. : Not established. : There is only a slow environmental degradation of the Product. : There is seemingly no tendency for bioaccumulation. : Unknown

#### 13 Disposal Considerations

- The following advice only applies to the product as supplied
- Combination with other materials may well indicate another route of disposal. If in doubt, contact local TLC-KOYA CHEMICALS MANUFACTURING SDN BHD or local authorities.
- Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor.
- Care should in any case be taken to ensure compliance with national and local regulations.
- This product is not suitable for disposal by either landfill or via municipal sewers, drains, and natural streams, rivers or seas, they will effect the relationaship between livings things, plants and their environment.

14 Transport information

General information

: This Product is not regulated for road/rail & sea transport.



MATERIAL SAFETY DATA SHEETPage :4P-611 HIGH TEMPERATURERevised edition no : 01BEARING GREASE(LITHIUM MP)Effective Date: 12-7-2014

## 15 Regulatory Information

Classification and labeling	: Classification /symbol - not regulated
Governing directive	: Occupational Safety and Health (Classification, Packaging and Labeling of
	Hazardous Chemicals) Regulations 1997
Safety advice	: (May contain information in excess of requirements under applicable laws.
	S23 Do not breathe gas/fumes/vapor/spray
	S24 Avoid contact with skin
	S33 Take precautionary measures against static discharges
	S62 If swallowed, do not induce vomiting: seek medical advice
	immediately and show this container or label.
6 Other information	
Further information	: None
Print date	: 12-7-2014
N/A - Not Applicable	N/D - Not Determined

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from data or test results obtained by us, are based on the current state of our knowledge at the time such reommendations are made. When additional information is obtained, these recommendations may be updated. They may also be influenced by circumstances outside our control. Notwithstanding such recommendations, the user is responsible to determine that the product as supplied by us, is suitable for the process or purpose he intends to use it. The user of the product is solely for compliance with all laws and regulation applying to the use of the product. Since we cannot control the application, use or processing of the products, we do not accept responsibility therefore. The user shall ensure that the intended use of the products will not infringe in any party's intellectual property rights.