

# PRODUCT SPECIFICATION

Page:1

Revised edition no: 01

# P-628 ANTI-TERMITE PAINT

Effective Date: 14-7-2014

# **Description:**

P-628 Anti-Termite Paint (Green), it is blend with used oil, resin and pigment for construction anti-dry wood termite application.

### **Specification**

Appearance : Thick Liquid Colour : Green

Binder Type : Specially modified with used oil, resin & pigment.

Drying Time : Touch Dry : 1.5 hrs

: Hard Dry : overnight

Consistency application : Ready for brush or roller application

Density : 1.1 - 1.3 Kg per Ltr

Recoating time : 1 hour
Thinning : Turpentine

Coverage : Approximately 8-10 sq m per Ltr.

Flash Point : below 80°C

Physical hazard : Flammable liquid UN 1263 Class 3

Note : This product same time may be out specification.

#### **Directions For Use**

It is necessary to ensure good surface preparation for maximum performance. The surface to be applied must be clean, dry and free from wax. Particular care must be given to previous waxed surfaces and thorough mechanical sending to remove the wax is recommended. Application can be use with roller or brush. Two coats are recommended to obtain the desired colour. Allow 1 hour drying time between coats.

### **Precautions**

Keep away from fire and food, Avoid prolonged contact with skin, if accidentally contact with eyes, and seek medical advice immediately.

## **Storage**

Store in cool place & away from fire & direct sunlight. Keep out of reach of children.

#### **Note**

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com