

PRODUCT SPECIFICATION

Page :1

Revised edition no: 01

P-634 TILE WORK ADHESIVE

Effective Date: 15-7-2014

Description:

P-634 Tile Work Adhesive is a polyvinyl modified cementationadhesive. It is specially blend for Tile Working for good adhesion. When mixing with normal cement, the two components will react chemically after mixing to from a hard and elastic coating film, which bonds firmly onto the substrate on application to protect against ingress of water.

Application

- To be added to water for dry mix process.
- Use at the rate of 2% by weight of cement.
- Cure at the concrete in normal way.

Physical Properties

Appearance : milky liquid
Odour : mild
Colour : milky white
Flash point : none

Non toxic, non corrosive, chloride free, non inflammable.

Precaution

Keep out of reach of children.

Storage

Store in cool & dry place. Avoid direct sunlight.

Packing

Packed into 4000ml, 20 Litres and 200 Litres.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com