



PRODUCT SPECIFICATION	Page :1
P-819	Revised edition no : 01
LATEX WATERPROOFING COMPOUND	Effective Date: 16-7-2014

Description:

A ready-mixed acrylic copolymer latex coating specially formulated for sealing cracks and joints on walls, ceilings and roofs by forming a tough continuous waterproof membrane. This thin membrane is exceptionally flexible, durable and weather resistant when dry.

Features & Benefits

- Waterproof
- Excellent elasticity
- Flexible
- Economical
- User friendly
- Environment Friendly
- No peel, crack even when subjected to extreme temperature and deteriorating element.
- High elongation of 300%. Allows the paint to accommodate "forthcoming hairline cracks" and movements on cracks due to serve temperature changes.
- Excellent adhesion to concrete and masonry surface.

Direction for Use

P-819 KOYA Latex Waterproofing Compound can be easily applied by using a brush or roller. On porous surface , dilute with 5% of water for the first coating. For the second coating, apply it undiluted. For optimum protection, a two coat application of P-819 KOYA Latex Waterproofing Compound is always recommended. Apply a second coat as soon as first coat is tack free.

Suitable Surface

P-819 KOYA Latex Waterproofing Compound can be applied to concrete, brick, bockwork, asphalt, asbestos cement, natural stone, concrete roof tiles, cement render, iron, galvanized steel, etc.

Coverage

Each kg of P-819 KOYA Latex Waterproofing Compound covers approximately 2 to 3sq.m per coat depending on the substrates.

Caution

Do not apply if rain, dew, gag or high humidity is expected within 2 hours of application.

Packing

1.5Kgs , 5Kgs & 24Kgs Pail.

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

TLC-KOYA CHEMICALS MANUFACTURING SDN BHD

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com