

GS3 Premium EC Pen Tester














3-color large LCD screen

- White for measurement mode
 - Green for calibration mode
 - Red for calibration error



The repalceable EC probe built with titanium alloy ensures high accuracy and takes minimal maintenance.





Simplest design allows you to complete calibration within 15 seconds to keep the highest accuracy.

Single-tap switch between EC, 500 ppm & 700 ppm

Lab-Grade Instruments Designed Specifically for Growers















Range	0 to 10.0 EC, 0 to 7000ppm (700ppm), 0 to 5000ppm (500ppm), 0 to 50°C (32 to 122°F)
Resolution	0.1 EC, 10ppm (700ppm), 10ppm(500ppm), 0.1°F/0.1°C
Accuracy	±0.1 EC ±30ppm (500ppm) ±40ppm (700ppm) ±1°C/±1°F
Temperature compensation	Automatic
Calibration	Automatic 1 point (2.77 EC)
Unit	EC, 500ppm, 700ppm, °F, °C
Power supply	4-AAA alkaline batteries
Backlight	White (measurement); Green (calibration); Red (errors)
Reading hold	Manual
Warranty	Two years for the instrument, one year for the probe
EC probe	Titanium alloy
Successful calibration indicators	M (2.77 EC)
Low battery reminder	
Waterproof rating	IP67
Reading stabilization icon	

What's in the box

