

TYRE TRANSPORT EQUIPMENT

Simple handling:

Spreading carrier spars can be operated by pressing the handle levers together. Easy movement of wheel or tyre stacks.



Combine with:

The TYRE TROLLEY including its load can be picked up by the tyre truck.

Smart solution:

TYRE TROLLEY with hardware skip for wheel and tyre stacks.



4546



4547



Example of use



Stackable



„TYRE TROLLEY“
4546

Smart dolly for easy transport and effective storage of normal-sized wheels and tyres. Designed for 8 tyres or 4 complete wheel sets. Practical hardware skip for storing small parts. Allows for easy and secure stacking. Compatible with the fetra tyre trucks 2032 and 2033. Platform made of fibreglass-reinforced polypropylene, 4 swivel castors with TPE tyres, one with lockable brake. Scaled pricing for 1/2/6 units.

„TYRE TROLLEY“
4547

Transport dolly for large wheels and tyres as they are used e.g. for SUVs. Castors with larger wheels facilitate transport on uneven surfaces.

Designed for 8 tyres or 4 complete wheel sets.

Practical hardware skip for storing small parts. Allows for easy and secure stacking.

Compatible with the fetra tyre trucks 2032 and 2033. Platform made of fibreglass-reinforced polypropylene, 4 swivel castors with solid rubber tyres, one with lockable brake.

Scaled pricing for 1/2/4 units.



Hardware skip

| | Order no. | Capacity kg | Wheel-Ø mm | Diameter mm | Height mm | Net weight kg | | | | |
|----------------|-----------|----------------|---------------|----------------|--------------|------------------|--|--|--|--|
| „TYRE TROLLEY“ | 4546 | 120 | 75 | 630 | 110 | 3,7 | | | | |
| | 4547 | 180 | 100 | 700 | 140 | 6,3 | | | | |



Tyre trucks

2032 | 2033

Welded tubular steel, powder coated blue RAL 5007, surface durably protected.

Wheels optionally with solid rubber or pneumatic tyres. Hubs with roller bearings.

By activating the hand grips, the truck spreads its carrier spars (made of tubular steel) so that the stack of tyres can be taken up and down directly. Suitable for tyres-Ø 450 to 750 mm. Up to 8 wheels and tyres possible.

Compatible with „TYRE TROLLEY“ 4546 and 4547.



2033 | 2033A

2032A | 2033A

as 2032 | 2033, but with pick-up rolls. Smoother picking up and putting down of wheel or tyre stacks. The carrier spars roll along the stack. Therefore significant reduced exertion of force for the user. Retrofittable for all fetra tyre trucks.

2034 | 2035

as 2032 | 2033, but for larger wheels and tyres like e.g. of SUVs. Suitable for tyres from 450 up to 860 mm Ø.

2034A | 2035A

as 2034 | 2035, but with pick-up rolls. Smoother picking up and putting down of wheel or tyre stacks. The carrier spars roll along the stack. Therefore significant reduced exertion of force for the user. Retrofittable for all fetra tyre trucks.



2035 | 2035A



Pick-up roll

| | Order no. | Capacity kg | Height mm | Lifting blade length mm | Lifting blade width mm | Total width mm | Solid rubber tyres mm | Pneumatic tyres mm | Net weight kg |
|---------------|-----------|-------------------------------------|-----------|-------------------------|------------------------|----------------|-----------------------|--------------------|---------------|
| Tyre trucks | 2032 | 200 | 1510 | 575 | 500 – 885 | 730 | 250 x 60 | – | 27,5 |
| | 2033 | 200 | 1510 | 575 | 500 – 885 | 730 | – | 260 x 85 | 24,5 |
| | 2032A | 200 | 1510 | 575 | 500 – 885 | 730 | 250 x 60 | – | 28 |
| | 2033A | 200 | 1510 | 575 | 500 – 885 | 730 | – | 260 x 85 | 25 |
| | 2034 | 200 | 1510 | 660 | 500 – 945 | 730 | 250 x 60 | – | 28,5 |
| | 2035 | 200 | 1510 | 660 | 500 – 945 | 730 | – | 260 x 85 | 25,5 |
| | 2034A | 200 | 1510 | 660 | 500 – 945 | 730 | 250 x 60 | – | 29 |
| | 2035A | 200 | 1510 | 660 | 500 – 945 | 730 | – | 260 x 85 | 26 |
| Pick-up rolls | E2034A | Add-on kit for existing tyre trucks | | | | | | | 0,5 |



4586



4596



4588



4562



Roller conveyor



Extended platform



Steps tilted

Tyre trolleys

Tubular steel and steel section construction, powder coated blue RAL 5007.

4586

Tyre carrier variable adjustable in intervals of 150 mm with clamps on the face ends.

For tyre diameter 250 - 750 mm.

4 swivel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel lock.

4596

Shelves with welded wire lattice 140 x 40 mm.

Carriers variably insertable within a distance of 120 mm. Due to the joint-like attachment, the carriers adapt automatically to the tyre size.

For tyre diameter 380 - 750 mm.

2 swivel and 2 fixed-wheel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel locks.

4588

As 4586, but reinforced version for heavy duty, e.g. for motor-sports as tyre trolley in pit lane.

For tyre diameter 400 - 780 mm.

4 swivel castors with blue-grey elastic tyres, hubs with ball bearing. 2 wheels with locks.

4562

For comfortable order picking of wheels and tyres. Tyre carrier with robust roller conveyors with fall through protection for easy moving of loaded wheels and tyres with 550 - 850 mm Ø.

Upper shelf screwable in height of 1.253 or 1.153 mm, capacity 80 kg.

At face ends 4 wooden steps lifting automatically when released and locking the trolley via rubber feet when under load. Safety stand on upper step by extended platform.

Safety handle to hold onto or lean against. The steps can be completely tilted assisted by a gas spring.

4 swivel castors, TPE tyres, hubs with groove ball bearing. Swivel castors with wheel lock.

| | Order no. | Capacity kg | Wheel-Ø mm | Platform size L x W mm | Outside dimensions L x W x H mm | Net weight kg |
|---------------|-----------|-------------|------------|------------------------|---------------------------------|---------------|
| Tyre trolleys | 4586 | 250 | 160 | 1420 x 600 | 1540 x 670 x 1725 | 40 |
| | 4596 | 400 | 200 | 1420 x 610 | 1600 x 620 x 1800 | 62 |
| | 4588 | 500 | 200 | 1860 x 618 | 1991 x 671 x 1671 | 62 |
| Tyre trolleys | 4562 | 250 | 125 | 1000 x 588 | 1343 x 625 x 1749 | 63 |

Accessories on page
184-185