



Overview

AZTC9288 Thermal & Optical Bi-spectrum Network

Camera, which is capable of highly accurate body temperature measurement, to within ± 0.3 °C. The camera features a built-in AI algorithm for multi-person measurements up to 3m distances, enabling fast and non-contact access. Perfect for adjunct use in hospitals, sub-acute health settings, public areas (i.e. airports), and more. Also can be widely used in close-range scene monitoring, such as indoor fire prevention, warehouse fire prevention, charging pile temperature monitoring and other fields



Large Mobility



High Volume Management





Cross Infection

Present Situation

During the epidemic, entrances and exits in public places basically use manual close-inquiries, manual body temperature measurement, manual registration, and personal mobile phone declarations as methods to prevent and control the epidemic. This management method requires a large number of staffs and staffs' self-protection standards are not uniform, which is easy to cause cross-infection. In addition, the information of the tested personnel is not comprehensive, and in the event of a new epidemic, there is no good trace ability mechanism.

Solution



Product Features

- High sensitivity thermal module with 256 x 192 resolution; NETD is less than 60 Mk (@25° C, F#=1.0);
- Supports contrast adjustment;
- Leading thermal image processing technology: Adaptive AGC, DDE, 3D DNR;
- Up to 15 palettes of adjustable color; Reliable temperature-anomaly alarm; Temperature Range From -15°C to +150°C ;
- Body Temperature Range From 35°C to + 50°C
- High quality optical module with 2 MP resolution; Bi-spectrum image fusion, picture-in-picture preview; Support for capture and save in PC of personnel in and out

Specification

Mode	AZTC9288
Thermal	
Image Sensor	Vox Uncooled Focal Plane Arrays
Resolution	256x192
Pixel Interval	12pm
NETD	Less than 60 mK (@25°C.F#=1.1)
Aperture	F1.0
Field of View	35° x 27° (H x V)
Optical	
Image Sensor	1/2.8" 2.0M Pixel CMOS
Resolution	1920x1080P
Min. Illumination	Color: 0.005Lux @ (F1.2, AGC ON), B/W 0.001 Ⅲ @ (F1.2,
Field of View	84° x 45° (H x V)
Focal Length	4mm
Shutter Speed	1s to 1/100,000s
White Balance	Auto/Manual/ATW (Auto-tracking White Balance)/Indoor/Outdoor/Daylight Lamp/Sodium Lamp
Day& Night	ModeIR cut filter with auto switch
WDR	80 dB
Feature	
Bi-spectrum Image Fusion	Fusion view of thermal view and overlaid details of the optical
Picture in Picture	Combines details of thermal and optical image PIP, overlay thermal image on optical image
Smart Function	
Face snapping	Built-in deep learning AI algorithm, Supports simultaneous detection of 20-30 faces
Temperature Measurement	Support global and local temperature
Temperature Range	From -15°C to +150°C
Body Temperature Range	From 35°C to + 50°C
Temperature Accuracy	Target temperature 35°C A 38°C ±0.3 °C Target temperature 20°C A 33°C ±0.6 °C Target temperature 38°C A 50°C ±0.6 °C
Network	
Main Stream	Thermal: 25fps(1920 x 1080, 1280 x 720)
Sub Stream	Thermal: 25fps(704 x 576, 352 x 288)
Video Compression	H.264 (Baseline/Main/High Profile) /MJPEG/H.265
Audio Compression	G 711u/G711a/G.7221/MP2L2/G.726/PCM
Protocols	TCP/IP, ONVIF, GB/T 28181, DHCP. RTP, RTSP,PPPoE
API	ONVIF (Profile S, Profile G, Profile T), SDK
General	
Web Client Language	languages English, Chinese
Power	DC 12V, 0.65A
Work Temperature/Humidity	From -20°C to 55°C; Humidity: 95% or Less
Protection Level	IP66
Dimension	246 mm x 101 mm x 81 mm (with bracket)
Weight	Approx. 1.0 kg



Airport



Metro



Commercial Building



School

AZTC9288 Thermal & Optical Bi-spectrum Network Bullet Camera can be used in Airport, Metro,

Commercial, School, support team to provide you with suitable solution.