

TOA MULTICHANNEL POWER AMPLIFIER DA-250F (CE301/CE-GB/CE-AU)

■ DESCRIPTION

The DA-250F is a 4-Channel Digital Power Amplifier featuring lightweight, compact, high power output, and high efficiency. It delivers 250 W \times 4 channels (4 Ω output) using a switching power supply. Each channel is equipped with an independent power section. It can be mounted in an EIA Standard equipment rack (1 unit size).

■ SPECIFICATIONS

*0 dB = 0.775 V

Power Source	220 - 240 V AC, 50/60 Hz
Amplification System	Class D
Power Consumption	294 W (based on EN standards)
, i	1200 W (rated output 4 Ω \times 4)
	800 W (rated output 8 Ω \times 4)
Input	4 circuits, +4 dB* (1.23 V) (input level control in maximum position),
	10 kΩ, electronically—balanced, removable terminal block (3 pins)
	CH 1 mode ON/OFF switch (ON: CH 1 to All ch, OFF: Each ch)
Rated Output	CH 1 mode ON/OFF switch (ON: CH 1 to All ch, OFF: Each ch) 4 channels: 250 W × 4 (4 Ω), 170 W × 4 (8 Ω)
, i	2 channels (BRIDGE): 500 W \times 2 (8 Ω)
	M4 screw terminal, distance between barriers: 8.8 mm (0.35")
Frequency Response	20 Hz - 20 kHz (±1 dB)
Total Harmonic Distortion	
	0.3 % (20 Hz - 20 kHz)
Protection Circuit	Protection against excessive current flow due to overload,
	short circuit, unusual DC voltage output,
	temperature rise at power amp. heat sink (110 °C (230 °F) or more),
	temperature rise inside the unit (80 °C (176 °F) or more)
S/N Ratio	100 dB (A-weighted)
Crosstalk	70 dB (A-weighted)
LED Indicator	Power (blue) × 1, Input (green) × 4, Output (yellow) × 4,
	Peak (red) × 4, Protect (red) × 4
Cooling	Forced air cooling
Operating Temperature	−10 °C to +40 °C (14 °F to 104 °F)
Operating Humidity	90 %RH or less (no condensation)
Finish	Panel: Aluminum, black, alumite
	Case: Plated steel sheet
Dimensions	482 (W) × 44 (H) × 401.8 (D) mm (18.98" × 1.73" × 15.82")
Weight	6.8 kg (14.99 lb)
Accessory	Power cord (2 m (6.56 ft)) ···1, Removable terminal plug (3 pins) ···4,
	Tamper—proof cap …4, Rack mounting screw (with plain washer) …4

