

# GTW

## Waterproof Weighing Scale



CE



ISO9001



**EXCELL**®

Since ▶ 1979

## FEATURES

### IP68 CERTIFIED BY SGS

- ◆ IP 68: mist-proof, waterproof and dustproof
- ◆ Up to 1/30,000 display resolution
- ◆ LCD display (Weight-6 digits); Full range tare; Auto zero tracking; Pre-tare
- ◆ High Speed 24bits AD; Display reading speed faster
- ◆ Faster weighing stability
- ◆ Zero key and Tare key react faster
- ◆ Preset weight or quantity; Weight accumulation
- ◆ Simple counting; Gross/Net indication; Hold function; Check mode Lo / Hi / OK
- ◆ Weight and quantity over-limit warning
- ◆ Pre-tare function
- ◆ Kilogram (kg) and pound (lb) weighing modes
- ◆ Stable sampling range setting function
- ◆ Built-in rechargeable battery
- ◆ Low power indication and auto power off
- ◆ RS-232 data-transfer interface
- ◆ U shape stand or Sleeve connecting stand selectable

# IP68



▼ U shape stand	▼ Sleeve connecting stand
	

## OPTION

- ◆ Wireless for distance 100M available (SPP mode supported)
- ◆ Relay output (3 sets relay output)
- ◆ 1/30,000 with temperature compensation component more accurate and stable

## SPECIFICATION

- ◆ Operating Temperature: Non-approval model: 0°C ~ 40°C (32°F ~ 104°F)  
Approval model: -10°C ~ 40°C (14°F ~ 104°F)
- ◆ Power Source: AC110V/230V (±10%) + DC 6V / 4Ah rechargeable battery
- ◆ Dimensions: 238 x 156 x 88mm (W x H x D)
- ◆ Display: LCD, 6 Digits, 25 mm (Height), LED backlight



**EXCELL**<sup>®</sup>  
Since 1979

## EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel +886 2 8919 1000 Website [www.excell-scale.com](http://www.excell-scale.com)

Fax +886 2 8919 1177 E-mail [sales@excell-scale.com](mailto:sales@excell-scale.com)