

DocuCentre-V C2265 / C2263

Easy to Operate, Easy to Collaborate.



Compact size with infinite possibilities

The DocuCentre-V C2265 / C2263 is embedded with a range of advanced features that can be adapted to all types of business environments. With a sleek

and compact design that is user and environmentally friendly your office can depend on this device for simple and seamless high-quality printing.

Impressive Print Quality

The DocuCentre-V C2265 / C2263 produces outstanding output with incredible clarity through industry leading colour printing.

Fuji Xerox has developed a high-precision, S-LED (Self-Scanning Light Emitting Diode) print head technology that achieves an output resolution of **1200 x 2400 dpi**.

With advanced IReCT (Image Registration Control Technology) it provides ultra high precision of 2400 dpi. This ensures highly accurate dot placement resulting in outstanding print quality.

Advanced Productivity Features

With multi-function capabilities this A3 device can handle your Print, Copy, Scan & Fax tasks efficiently. To ensure versatility, optional add-ons such as our advanced finishers can enhance your office productivity levels significantly by taking charge of timeconsuming jobs, such as stapling, booklet making and hole punching.



Intuitive 7-inch touch screen that supports Flick/Drag operations. The fully customisable menu allows the user to tailor items to their needs, increasing productivity.

| 0 | MARKE | Elegent descentes | | | |
|----------------|----------------|-------------------|------------------|---|---------|
| | DocuCentre-V | DocuCentre-V | Basclerity VCDSS | | Carno C |
| | C2265 | C2263 | | 5 | 1 |
| Print | 25ppm | 20ppm | | | |
| Сору | 25ppm | 20ppm | RUINITION D | | 2 |
| Scan | 55ppm | 55ppm | | | 3 |
| Fax (Optional) | Super G3 suppo | orted | 5 | | |

The DocuCentre-V C2265 / C2263 is scalable from 596 pages standard paper input up to a maximum of 2,096 pages.



Business Mobility

Users are no longer restricted to printing documents only from their desktop PC's. Fuji Xerox products are certified with various wireless printing utilities that allow you to seamlessly print from your smartphone or tablet device.

Fuji Xerox Print Utility

You can improve your work efficiency by using mobile devices in conjunction with Fuji Xerox MFPs, printers and softwares. The Print utility allows you to print websites, photos, emails and more, directly from your iOS or Android mobile device. You can also scan documents and send to your mobile device directly from the DocuCentre-V C2265 / C2263.

Mopria[®] Alliance Certification

Fuji Xerox Printers has gained Mopria Alliance certification for the DocuCentre-V C2265 / C2263, making it possible for Android users to easily print documents using their smartphone and tablet devices. Printing from your smartphone, is as simple as printing from a computer. Mopria Print Service can be downloaded for free from Google Play[™] Store (Android[™] 4.4 or later).

AirPrint

AirPrint is a built-in iOS offering that allows users with ownership of a Mac, iPhone, iPad or iPod Touch to print full quality media files from their devices without the need to install a third party software. To print from an iOS device all you need is a secure Wi-Fi network.

Google Cloud Print

In the world of Google Cloud Print, you can print anything, from any device, to any cloudconnected printer.

When you print through Google Cloud Print, your file is securely transferred to your printer over the web. Since it's the web, Google Cloud Print works whether you're in the same room as your printer, or on another continent.

Google Cloud Print is a web printing service from Google.

Cloud on-demand print (optional)

Using the cloud service on the internet enables you to print on a multifunction device at your destination. Cloud on-demand printing is the solution for any office, it eliminates the need for users to install a printer driver on their PC and saves data automatically, reducing the risk of losing files carried on a USB.

Simply Connected – Wi-Fi Direct (Concurrent Mode)

Wi Fi 1 Wi-Fi Connection. Connects to MFDs via an access point 2 Wi-Fi Direct Connection. (Wi Fi) Does not need an access point. DIRECT Connects directly from the Wi-Fi device to the MFD can be connected MFD Wifi Connection via Access Wireless LAN Converter Access Point not needed, Wifi Direct Connection Access Point Wireless Router Network Wifi Mobile Devices Devices

Productive, easy to use, and practical for your business

With advanced scan functionality, document security and workflow choices, the DocuCentre-V C2265 / C2263 is designed to maximise productivity in your work space. In addition, our innovative technology ensures our users can enjoy server-less on demand printing.

My scanning

The standard duplex automatic document feeder (DADF) is capable of stacking up to 110 sheets that allows for rapid duplex scanning of 55ppm.

With customisable settings, individual users can automatically send scanned files to their email address without the hassle of continuously changing the scan settings.

When scanning documents, users can also insert a USB to save these documents or alternatively print supported documents from the USB. Users can also store or print from USB devices.

Scan Delivery (Option)

For group or departmental use, all scan settings and scan destinations are preconfigured by the IT administrator so users can scan and save data to a specified folder automatically just by selecting a prepared button for each document type, such as invoices, purchase orders, quotes, and so forth. This ensures documents are saved in the right location and in the right file formats for easy archival and/or use with other business systems.



Scanned data is automatically sent to the specified folder.




Server-less Authentication

Security and controlling access to the device is critical in many business environments. Server-less authentication allows users to be pre-registered on a MFD to access the device. This allows the user to access other devices without the need of a server for multiple device environments. Server-less authentication allows users access to multiple devices without the need of a server. For convenience, the optional embedded IC card reader can be installed and your organisation can utilise existing proximity card readers for building access with the DocuCentre-V C2265/C2263 range.

Server-less on demand print

Fuji Xerox provides the follow-you printing function that does not require a server. This optional function is made possible by linkage between other multifunction devices on a network. On top of this, initial investments can be significantly reduced because there is no need to incorporate a dedicated server. This contributes to the reduced number of devices by increasing the utilisation rate of devices and is convenient for use in small to large scale offices.








Environmentally friendly

Fuji Xerox is committed to helping our customers become more sustainable. Our technology and services are designed to improve sustainability performance for our customers.

The DocuCentre-V C2265 / C2263 complies with the International ENERGY STAR® Program and has energy efficient components to reduce our users impact. With an environmentally responsible design, such as some components are created using 'non-edible biomass plastics' that is strong, non-flammable and simultaneously reduces carbon emissions.

Smart Energy Management


This feature reduces power consumption and CO_2 emissions by supplying power only to to the components that are being used. For example, during scanning activities no power is supplied to other parts of the device.



Reducing power consumption

With our clever product design, the cooling fan within the device is completely stopped when in standby mode. This decreases energy consumption and significantly reduces noise levels.

In sleep mode the devices consumes less than 1.0 W of power, in comparison to when working at its optimal level the DocuCentre-V C2265 / C2263 uses 1.76 kW of power.






With a power save button on the control panel, this ensures that during inactivity the devices are preserving power. However, when needed the control panel becomes active in 3 seconds to ensure it is always ready. Such features help your offices save money whilst reducing your carbon footprint.

Waste-free Fax

Incoming fax documents are immediately placed into a folder on the devices, and are only printed when users select to do so. This reduces unnecessary print jobs, and decreases paper and toner wastage. Administrators can also block incoming faxes from particular contacts or anonymous numbers.



Direct Fax users can send faxes directly from their PC's. Fax documents also have the option to be saved as a PDF and sent as an e-mail attachment.

Overview of the DocuCentre-V C2265 / C2263

The DocuCentre-V C2265 / C2263 is a versatile and robust office partner loaded with the latest technology to optimise your office productivity. Giving you all the

functionalities of an A3 multi-function device plus the option to add a professional finisher so your documents can stand out.



 Duplex Automatic Document Feeder

Stack up to 110 sheets, and scan mixed sized originals at up to 55ppm

Intuitive Control panel

7" colour touch screen with easy to use operations

3 Fax Function (optional)

In-built Storage

Store and access your documents with the in-built 160GB HDD

5 Versatile paper trays

Up to 4 trays, up to 2,096 sheets.

6 Hole Punch Unit

Save time on presenting your important copies with 2, 3, or 4 hole punches at a touch of a button

Booklet Finishing

Bringing in our advanced finishing such as Saddle Staple and Scoring for paper sizes A4 through to A3.

8 Advanced Finisher

Stack up to 2,000 sheets of paper and staple up to 50 sheets in multiple positions in a variety of paper weights.

Bypass tray

Holds up to 96 sheets, up to 216 gsm



High productivity with our advanced finishing

The DocuCentre-V C2265 / C2263 is a powerful addition to any office. For optimal productivity, pair with any of our advanced finishing options to take your documents to the next level. From stapling, hole-punching to booklet making, ensure easy to use and effortless professional-level documents at your fingertips. Finisher - A1 (Optional) Finisher - B1 (Optional) This inbuilt component is perfect for For more advanced finishing options, customers who have limited office space this has the capability to print booklets, and require a simple stapling option. staple in multiple positions and holepunch a range of documents. Stapling Stapling up to 50 sheets A4 Stapling up to 50 sheets in 1 position. (Dual stapling A4 in 3 positions only available in B1) Single Staple Top L Single Staple Top R Dual Stapling Hole Punch Hole punching paper up to 200gsm (requires the hole-punch unit) 3-Hole Punch 2-hole Punch 4-hole Punch (U.S Spec) **Booklet Making** (Left to Right) (Right to Left) (Top) Saddle stapling up to 15 sheets, booklet finishing and fold (requires the booklet maker unit) Saddle Stapling and Fold Booklet Finishing

Specifications of DocuCentre-V C2265 / C2263

Basic Specifications/Copy Function

| Item | | DocuCentre-V C2265 | DocuCentre-V C2263 | |
|--------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--|
| Туре | | Desktop / Console | | |
| Memory capacity | | 4 GB (Max: 4 GB) | | |
| Hard disk capacity*1 | | 160 GB standard, or larger (Usable sp | ace: 128 GB) | |
| Colour Capability | | Full Colour | | |
| Scan Resolution | | 600 x 600 dpi | | |
| Printing Resolution | | 1200 x 2400 dpi | | |
| Warm-up Tin | ne | 30 seconds or less, 22 seconds or less if the r | nain power is on (At room temperature 23°C | |
| Original Size | | Maximum of 297 x 432 mm (A3, 11 x 17") for both Sheet and Book | | |
| | Max | A3, 11 x 17" | | |
| Paper Size | Min | A5 [Postcard (100 x 148 mm) and Envelope Monarch (191 x 98 mm) when using Bypass Tray] | | |
| | Image loss width | Lead Edge 4.0 mm, Trail Edge 2.0 mm, Right & Left Edges 2.0 mm | | |
| Paper | Paper Tray | 60 to 256 gsm | | |
| Weight*2 | Bypass Tray | 60 to 216 gsm | | |
| First Copy Output | B/W*3 | 5.9 sec. | | |
| Time | Colour*4 | 8.1 sec. | | |
| | A4 LEF / B5 LEF | B/W: 25 ppm, Colour: 25 ppm | B/W: 20 ppm, Colour: 20 ppm | |
| Continuous | A4 | B/W: 19 ppm, Colour: 19 ppm | B/W: 16 ppm, Colour: 16 ppm | |
| Сору | B5 | B/W: 14 ppm, Colour: 14 ppm | B/W: 11 ppm, Colour: 11 ppm | |
| Speed*5 | B4 | B/W: 16 ppm, Colour: 16 ppm | B/W: 13 ppm, Colour: 13 ppm | |
| | A3 | B/W: 14 ppm, Colour: 14 ppm | B/W: 11 ppm, Colour: 11 ppm | |
| | Standard | 500 sheets x 1-tray + Bypass Tray 96 sheets | | |
| Paper Tray Capacity* ⁶ | Optional | 1 Tray Module / 1 Tray Module with Cabinet: 500 sheets x 1-tray 3 Tray Module: 500 sheets x 3-tray | | |
| | Max | 2096 sheets [Standard + 3 Tray Module] | | |
| Output Tray | Capacity*7 | Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF) | | |
| Power Supply | | AC220-240 V +/- 10 %, 8 A, 50/60 Hz common | | |
| Maximum Power Consumption | | 1.76 kW or less (AC220 V +/- 10%), 1.92 kW or less (AC240 V +/- 10%) Sleep Mode: 1.0 W or less (AC220 V +/- 10%) Ready Mode: 78 W or less (AC220 V +/- 10%) | | |
| Dimensions | | W 590 x D 659 x H 768 mm W 590 x D 659 x H 962 mm (when optional 1 Tray Module is installed.) W 616 x D 659 x H 1119 mm (when optional 1 Tray Module with cabinet is installed.) W 616 x D 659 x H 1119 mm (when optional 3 Tray Module is installed.) | | |
| Weight*8 | | 68 kg 87 kg (when optional 1 Tray Module is 92 kg (when optional 1 Tray Module v 95 kg (when optional 3 Tray Module is | vith cabinet is installed.) | |

*1: The Storage Hard disk capacity is not totally available for customers, *2: It is recommended to use Fuji Xerox recommended paper. Correct print output may not be possible depending on the requirement. *3: A4 LEF / Monochrome priority mode, *2: The speed may be reduced due to the image quality adjustment. *6: 80 gsm paper. *7: 64 gsm paper. *8: Excluding Toner Cartridge.

Print Function

| Item | | Description |
|----------------------------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Туре | | Built-in type |
| Continuous Print Speed*1 | | Same as the Basic Specifications / Copy Function |
| Printing Resolution | | 600 x 600 dpi, 1200 x 2400 dpi |
| Page | Standard | PCL5 / PCL6 |
| Description Language | Optional | Adobe® PostScript® 3™ |
| Supported Operating System | Standard (PCL Driver) | Windows® 10 (32bit), Windows® 10 (64bit), Windows® 8.1 (32bit) Windows® 8.1 (64bit), Windows® 8 (32bit), Windows® 8 (64bit) Windows® 7 (32bit), Windows® 7 (64bit), Windows Vista® (32bit) Windows Vista® (64bit), Windows Server® 2012 R2 (64bit) Windows Server® 2012 (64bit), Windows Server® 2008 R2 (64bit) Windows Server® 2008 (32bit), Windows Server® 2008 (64bit) Windows Server® 2003 (32bit), Windows Server® 2003 (64bit) |
| | Standard (Mac OS X Driver) | OS X 10.10/10.9/10.8, Mac OS X 10.7/10.6/10.5 |
| | Optional (Adobe® PostScript® 3™ Driver) | Windows® 10 (32bit), Windows® 10 (64bit), Windows® 8.1 (32bit) Windows® 8.1 (64bit), Windows® 8 (32bit), Windows® 8 (64bit) Windows V (32bit), Windows® 7 (64bit), Windows Vista® (32bit) Windows Vista® (64bit), Windows Server® 2012 R2 (64bit) Windows Server® 2012 (64bit), Windows Server® 2008 R2 (64bit) Windows Server® 2008 (32bit), Windows Server® 2008 (64bit) Windows Server® 2003 (32bit), Windows Server® 2008 (64bit) Windows Server® 2003 (32bit), Windows Server® 2008 (64bit) O S X 10.101.09./10.8, Mac OS X 10.7/10.6/10.5 |
| Interface | Standard | Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB2.0 |

depending on the document.

| Side Tray (Optional) | | | |
|----------------------|--------------------------|--|--|
| Item | Description | | |
| Paper Capacity*1 | 100 sheets | | |
| Dimensions | W 353 x D 429 x H 198 mm | | |
| *1: 64 gsm paper. | | | |

Notes

If the storage media (such as hard disk drives) of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall Fuji Xerox be liable for any damages whatsoever arising from loss of data.
Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

The product specifications, appearance and other details in this brochure are subject to change without notice for improvements.

All product names and company names mentioned in this brochure are trademarks or registered trademarks of their respective companies.

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law : Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc. Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

For more information or detailed product specification, please call or visit us at

Fuji Xerox Asia Pacific Pte Ltd

14a Rodborough Road Frenchs Forest NSW 2086 Australia 1300 793 769 New Zealand 0800 993 769 www.fujixeroxprinters.com.au www.fujixeroxprinters.co.nz

Scan Function

| Item | | Description | |
|-----------------------------------------------------------|-------------------------------------|-----------------------------------------------------------------------------------------|--|
| Туре | | Colour Scanner | |
| Scan Resolu | ition | 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi | |
| Scan Speed*1 | Duplex Automatic Document Feeder | B/W: 55 ppm, Colour: 55 ppm [Fuji Xerox Standard Paper (A4 LEF), 200dpi, to Folder.] | |
| Interface | Standard | Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T | |
| *1: The scanning speed varies depending on the documents. | | | |
| Fax Function (Optional) | | | |
| Item | | Description | |
| | | | |

| Original Size | Max: A3, 11 x 17", Long document (Longest 600 mm) | |
|------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|--|
| Recording Paper Size | Max: A3, 11 x 17" Min: A5 | |
| Transmission Time | 2 seconds and more but fewer than 3 seconds*1 | |
| Transmission Mode | ITU-T G3 | |
| Applicable Lines | Telephone subscriber line, PBX, Fax communication (PSTN), Maximum 3 ports*2 (G3-3 ports) | |
| *1: When A/s size desument with approximately 700 characters is transmitted in standard image auglity (8 y | | |

*1: When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 385 lines / mm) and in high-speed mode (28.8 kbps or faster, IBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contensio f the document, the type of machine receiving the fax, and line condition. "2: No.61 FAX lines is up to 3 ports. Port refers to number of channels for FAX.

Duplex Automatic Document Feeder

| Item | DocuCentre-V C2265 | DocuCentre-V C2263 | |
|-------------------|---------------------------|------------------------------------------|--|
| Original Size | Max: A3, 11 x 17" Min: A5 | *1 | |
| Paper Weight | 38 to 128 gsm (In Duplex | 38 to 128 gsm (In Duplex: 50 to 128 gsm) | |
| Capacity*2 | 110 sheets | | |
| Feeding Speed | B/W: 25 ppm | B/W: 20 ppm | |
| (A4 FF Simplex) | Colour: 25 ppm | Colour: 20 ppm | |

*1: The minimum custom size is 125 x 85 mm. *2: 64 gsm paper.

Finisher-A1 (Optional)

| Item | | Description |
|---------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Туре | | Sort (Offset available) / Stack (Offset available) |
| Paper Size | | Max: A3, 11 x 17" Min: Postcard (100 x 148 mm) |
| Paper Weight | | 60 to 220 gsm |
| Paper Capacity*1 | Finishing Tray | [Without Stapling] A4: 500 sheets, B4: 250 sheets, A3 or larger: 200 sheets, Mixed Size Stacking ^{r2} : 250 sheets [With Stapling] 30 sets |
| Staple | Capacity | A4: 50 sheets (90 gsm or less), B4 or larger: 30 sheets (90 gsm or less) |
| | Paper Size | Max: A3, 11 x 17" Min: B5 LEF |
| | Position | Single stapling |
| Dimensions | | W 559 x D 448 x H 246 mm |
| Weight | | 12 kg |

*1: 64 gsm paper. *2: When larger size sheets are stacked on top of smaller size sheets.

Finisher-B1 (Optional)

| Item | | Description | |
|------------------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Туре | | Sort (Offset available) / Stack (Offset available) | |
| Paper Size*1 | | Max: A3, 11 x 17" Min: B5 LEF | |
| Paper Weight | | 60 to 220 gsm | |
| Paper Capacity*2 | | [Without Stapling] A4: 2000 sheets, B4 or larger: 1000 sheets, Mixed Size Stacking ⁴³ : 300 sheets (With Stapling] A4: 100 sets or 1000 sheets ⁴⁴ , B4 or larger: 75 sets or 750 sheets [With Booklet Finishing ⁴⁵] 50 sets or 600 sheets [With Scoring ⁴⁵] 500 sheets | |
| | Capacity | 50 sheets (90 gsm or less) | |
| Staple | Paper Size | Max: A3, 11 x 17" Min: B5 LEF | |
| | Position | Single stapling or Dual stapling | |
| D 1 *6 | Number of Holes | 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications) | |
| Punch*6 | Paper Size | A3, 11 x 17", B4, A4*7 , A4 LEF, Letter*7 , Letter LEF, B5 LEF | |
| | Paper Weight | 60 to 200 gsm | |
| Booklet Finishing* ⁵ | Capacity | Saddle Staple: 15 sheets, Scoring: 5 sheets | |
| | Paper Size | Max: A3, 11 x 17" Min: A4, Letter | |
| | Paper Weight | Saddle Staple: 64 to 80 gsm, Scoring: 64 to 105 gsm | |
| Dimensions | | W 657 x D 552 x H 1011 mm, With Booklet Finisher: W 657 x D 597 x H 1081 mm | |
| Weight | | 28 kg, With Booklet Finisher: 37 kg | |
| Mater Finish an | D1 :=ill | al contrar a settion of 4 Terror Mandula contable Carbin at an 2 Terror Mandula in other share to a | |

Weight 28 kg. With Booklet Finisher: 37 kg Note: Finisher-B1 is available only when optional Tiray Module with Cabinet or 3 Tray Module is attached to Main Unit. "1: Paper size is smaller than B5, and larger than A3, 11 x 17" can be output from the Center Tray. "2:64 gam paper." 3: When larger size sheets are stacked on top of smaller size sheets. "4: 75 sets or 750 sheets with dual stapling. "5: The Booklet Finishing function requires the optional Finisher-B1 Booklet unit. After a job with the Booklet Finishing function specified has been output, the next job may not be delivered until the sheets are removed from the output tray. As, if larger size sheets are stacked on top of smaller size sheets sheets after a job with the Booklet Finishing function specified has been run, the next job may not be delivered until the sheets are removed from the output tray. "6: The Punch function requires the optional Finisher-B1 Punch unit for 2-hole / 4-hole punch or Finisher-B1 Punch unit for 2-hole / 3-hole punch (US Specifications)." 7: 3-hole punch is not applicable.



