

The **MicroMate** Static Power Inverter is Manufactured using proven CPU controlled high frequency PWM technology which provides highest level of reliability to meet the demand of today's telecommunications market. The inverting process offers efficiencies greater than 88% over the normal load range. In addition to reducing direct energy consumption, the cost of environmental conditioning is minimized. The pure sinewave inverter has extremely low electrical noise levels and thus is ideal for use in low noise applications.

The product meets all DC requirements of the ECC specification on DC weighted noise levels along with the relevant industrial standards. It is environmental friendly, high energy efficient, and equipped with all necessary features such as Thermal Protection, Output Over Current / Short-Circuit Protection, DC Low Pre-warning Buzzer and Auto Cut-Off and Status LEDs.

MicroMate®

2000W Pure Sinewave Static Power Inverter

TECHNICAL SPECIFICATIONS

Model	SN2000-12
Power Rated	2000W
Max Power	2050W
Peak Power	4000W
Output Current	8.7A _{max}
Input Data	DC 12V ±10%
Output Data	AC 230V ±3% (selectable 220V/240V), 1-ph, 50Hz ±0.1%
Waveform	Pure Sinewave
Output Distortion	≤ 3% THD (linear load)
Efficiency	>88%
Indications	LED for operating status and fault indication
Protection	Over Load, short circuit, over / low voltage
Cooling	Force Cooling
Ambient Temp.	-10°C ~ +50°C
Humidity	0 ~ 95% without condensation
Dimensions	W168 x D300 x H80 mm ³
Weight	3.8KG



* Due to the policy of continued product improvement, specifications are subject to change without notice.



Authorised Channel



EMERGING COMPANY
BUSINESS OF THE YEAR
MALAYSIA 2005



CRYSTAL WINNER
BUSINESS SUMMIT
MALAYSIA 2007



INTERNATIONAL GOLD STAR
FOR QUALITY AWARD
(ISQA), GENEVA 2008



KECERMELANGAN PERNIAGAAN BERETIKA
MINISTRY OF DOMESTIC TRADE
CONSUMER AFFAIRS MALAYSIA 2010

