

T-Fresh





























Quick Cooling /Heating

Closed Louver Design

Refrigerant Lacking Protection

Intelligent& Controllable Electric Heating

Intelligent Defrosting Monitor

LED Display

Closed Structure Auto Restart of Connection Pipe Outlet

Turbo Cooling **Auto Clean**

- Large air flow & rapid cooling
- Cross fan continues blowing to dry indoor unit inside after switched off, to keep clean and healthy.







T-FRESH

Simple Design Brings Life To Its Original Nature



Beautiful Integrated Design



Precise Air Guiding



Concealed Display Screen and Touch Control Button

Model			GVC24AL-K6NNC7A	GVC48AL-M6NNC7A
Cooling Conscitu		kW	7.00	12.31
Cooling Capacity		Btu/h	23,884	42,000
COP		W/W	2.80	2.80
EER		Btu/h/W	9.55	9.55
Power Supply		Ph,V,Hz	1Ph, 220-240V, 50Hz	3Ph, 380-415V, 50Hz
Power Input	Cooling	W	2500	4390
Rated Current	Cooling	A	18.00	9.55
Refrigerant Charge Volume		kg / oz	1.62 / 49.4	2.30 / 81.1
Indoor Unit			GVC24AL-M6NNC7A/I	GVC48AL-M6NNC7A/I
Airflow Volume		m³/h	1000 / 800 / 710 / 600	1900 / 1850 / 1700 / 1530
Airriow volume		CFM	547 / 471 / 418 /353	1118 / 1089 / 1000 / 900
Sound Pressure Level	Indoor	dB(A)(SH/H/M/L)	46 / 44 / 41 / 38	53 /50 / 48 / 45
Outline Dimension	WxHxD	mm	507 x 1770 x 320	587 x 1882 x 394
Weight/Gross Weight	Indoor	kg	38.5/52	55/77.5
Outdoor Unit			GVC24AL-M6NNC7A/O	GVC48AL-M6NNC7A/O
Sound Pressure Level	Outdoor	dB(A)	57	59
Outline Dimension	WxHxD	mm	963 x 700 x 396	1032 x 1250 x 412
Weight/Gross Weight	Outdoor	kg	60/64.5	107/118
Connection Pipe	Gas	mm / inch	12.70 / 1/2"	15.88 / 5/8"
	Liquid	mm / inch	6.35 / 1/4"	9.52 / 3/8"
	Max	Height m /ft	20 / 65.6	20 / 65.6
	Distance	Length m/ft	25 / 82.0	30 / 98.4
	Length	m/ft	7.5 / 24.6	7.5 / 24.6
	Gas Additional	g/m	12.00	12.00
	Charge	oz/ft	0.129	0.129
Refrigerant			R32	R32