



TEXFOOD HYDRA 32, 46, 68, 100

HIGH PERFORMANCE FOOD GRADE HYDRAULIC OIL



DESCRIPTION

LUBTEX® TEXFOOD HYDRA are food grade, non-toxic, developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

OUTSTANDING FEATURES

- Low coefficient of friction provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals
- Low foaming reduces residue and scum build-up, which extends maintenance intervals

DIRECTION FOR USE

LUBTEX® TEXFOOD HYDRA are suitable for hydraulic systems designed to operate in applications where ISO 32, 46, 68 and 100 oil viscosity grades are used. Follow manufacturer's instructions.

It is important to purge the system of the previous oil prior to recharging with LUBTEX® TEXFOOD HYDRA.

Technical Data (typical values)	TEXFOOD HYDRA 32 46 68 100			
Viscosity @ 40 °C (ISO 3104)	32	46	68	100
Viscosity @ 100 °C (ISO 3104)	5.8	7.5	9.9	13.0
Viscosity Index (ISO 2909)	125	128	128	127
Appearance	Clear Fluid			
Base Fluid	Blend of Synthetic oils			
Temperature range: (depending on the grade)	-15°C to +150°C			
Flash Point (ISO 2592)	220	220	222	224

*The content of this data sheet given in good faith but without warranty