



SIRIM QAS International Sdn. Bhd.
(Company No.: 199601037981 (410334-X))
No.1, Persiaran Dato' Menteri, P.O.BOX 7035, Section 2,
40700 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: 03-55445872
Fax: 03-55445886
www.sirim-qas.com.my

TEST REPORT

| | |
|--|---------------|
| REPORT NO : 2022CB0686 | PAGE : 1 OF 7 |
| This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report. | |

THIS TEST REPORT IS ISSUED IN SECURED PDF SOFTCOPY

Applicant : SCIN CHEM PRODUCTS SDN. BHD.
No: 1, Jalan Woo Ten,
42000 Pelabuhan Klang
Selangor.

Manufacturer : SCIN CHEM PRODUCTS SDN. BHD.

Product : SCP Skim Top Coat

Reference Standard / Method of Test : BS EN 998-1: 2016,
Specification for mortar for masonry. Part 1: Rendering and Plastering mortar
Clause 5.2: Characteristics of fresh mortars
Clause 5.3: Characteristics of hardened mortars

Description of sample : One (1) bag of 15 kg SCP Skim Topcoat and two (2) pieces of concrete slab
coated with SCP Skim Topcoat of size 400 mm x 300 mm x 40 mm were
received for testing.
Brand: SCP
Product Description: Dry mixed powder

Date Received of Complete Application : 18 July 2022

Job No. : J20221430473

Description of Test Results : This test report covers only test clauses as requested by Applicant to SIRIM
QAS International Sdn. Bhd. The test results for the submitted test samples
as described in this test report complied with the requirements of the above
reference standard at the respective clauses tested.

Issued Date : 07 October 2022

Approved Signatory;

(HANON NAZIR BIN MOHD BASRI)
Senior Testing Executive



(RAJANOR SIHA BINTI RAJA ABDUL HANAN)
Head
Civil & Construction Section
Testing Services Department

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

TEST RESULTS:

Product : SCP Skim Top Coat
 Mix ratio : 36 % of water
 Method of test : 1) BS EN 998-1-2016,
 Specification for mortar for masonry. Part 1: Rendering and plastering mortar
 2) BS EN 1015-7: 1999,
 Methods of test for mortar for masonry – Part 7: Determination of air content of fresh mortar
 3) BS EN 1015-9: 1999,
 Methods of test for mortar for masonry – Part 9: Determination of workable life and correction time of fresh mortar
 4) BS EN 1015-3: 1999,
 Methods of test for mortar for masonry – Part 3: Determination of consistence of fresh mortar (by flow table)

| CLAUSE | TEST METHOD/REQUIREMENT | TEST RESULTS | REMARK* |
|--------------|---|---|--------------------------|
| 5.2 5.2.1 | Characteristics of fresh mortar Workable Life The workable life shall be declared by the manufacturer - Method A: Workable Life of General-Purpose mortar The workable life shall be declared by the manufacturer and measured by time in minutes by which it reaches the limit of resistance to penetration. - Method B: Workable life of thin layer mortar The workable life shall be declared by the manufacturer and measured by the time in minutes which flow value of mortar differs by 30 mm. | <u>Workable life (Stiffening time)</u> Resistance at 0.5 N/mm ² : 400 minutes <u>Workable life by flow table</u> 185 minutes | Declared by manufacturer |
| 5.2.2 | Air Content The air content shall fall as declared by the manufacturer - Method A: Pressure Methods Declared range of value: 10% – 15% | <u>Air Content</u> 1) 13.0 % 2) 13.0 % Mean: 13.0 % | Pass |

Note:

1) Testing period – 9th August 2022 to 30th September 2022.

2) *Simple Acceptance Rule is used for the conformity statement. The level of risk regarding the Probability of False Accept is up to 50% according to ILAC G8:09.



This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

TEST RESULTS:

Product : SCP Skim Top Coat
 Mix ratio : 36 % of water
 Method of test : 1) BS EN 998-1-2016,
 Specification for mortar for masonry. Part 1: Rendering and plastering mortar
 2) BS EN 1015-10: 1999,
 Methods of test for mortar for masonry – Part 10: Determination of dry bulk density of hardened mortar

| CLAUSE | TEST METHOD/REQUIREMENT | TEST RESULTS | REMARK |
|--------------|--|--|--------|
| 5.3 5.3.1 | Characteristics of hardened mortar General The properties relevant to the intended use and/or type of product shall be declared. GP: General purpose rendering/plastering mortar L1: Dry Bulk Density Declared range of value: 1200 kg/m ³ to 1500 kg/m ³ . | <u>Dry Bulk density</u> 1) 1320 kg/m ³ 2) 1350 kg/m ³ 3) 1320 kg/m ³ Mean: 1330 kg/m ³ - nearest 10 kg/m ³ | Pass |

Note:

1) Testing period – 9th August 2022 to 30th September 2022.

2) *Simple Acceptance Rule is used for the conformity statement. The level of risk regarding the Probability of False Accept is up to 50% according to ILAC G8:09.

The remainder of this page is intentionally left blank)



This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

TEST RESULTS:

Product : SCP Skim Top Coat
 Mix ratio : 36 % of water
 Method of Test : 1) BS EN 998-1-2016,
 Specification for mortar for masonry. Part 1: Rendering and plastering mortar
 2) BS EN 1015-11: 1999,
 Methods of test for mortar for masonry – Part 11: Determination of flexural and compressive strength of hardened mortar

| CLAUSE | TEST METHOD/REQUIREMENT | TEST RESULTS | REMARK |
|--------------|---|---|--------|
| 5.3 5.3.1 | Characteristics of hardened mortar General Classification for hardened mortar properties. GP: General purpose rendering/plastering mortar L2: Compressive strength Range of Compressive strength at 28 days - Categories CS IV: $\geq 6.0 \text{ N/mm}^2$ | <u>Flexural Strength</u> 1) 4.1 N/mm^2 2) 4.3 N/mm^2 3) 4.2 N/mm^2 Mean: 4.2 N/mm^2 <u>Compressive Strength</u> 1) 13.0 N/mm^2 2) 12.0 N/mm^2 3) 11.4 N/mm^2 4) 12.9 N/mm^2 5) 13.3 N/mm^2 6) 13.7 N/mm^2 Mean: 12.7 N/mm^2 | Pass |

Note:

1) Testing period – 9th August 2022 to 30th September 2022.

2) *Simple Acceptance Rule is used for the conformity statement. The level of risk regarding the Probability of False Accept is up to 50% according to ILAC G8:09.



| | | |
|--|--|--|
| | | |
|--|--|--|

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

TEST RESULTS:

Product : SCP Skim Top Coat
 Mix ratio : 36 % of water
 Method of Test : 1) BS EN 998-1-2016,
 Specification for mortar for masonry. Part 1: Rendering and plastering mortar
 2) BS EN 1015-12: 2016,
 Methods of test for mortar for masonry – Part 12: Determination of adhesive strength of hardened rendering and plastering mortars on substrates

| CLAUSE | TEST METHOD/REQUIREMENT | TEST RESULTS | REMARK |
|--------------|---|---|--------|
| 5.3 5.3.1 | Properties of hardened mortar General The properties relevant to the intended use and/or type of product shall be declared. GP: General purpose rendering/plastering mortar L3: Adhesion Declared value: $\geq 0.3 \text{ N/mm}^2$ | <u>Adhesion Strength</u> 1) 0.29 N/mm^2 2) 0.34 N/mm^2 3) 0.45 N/mm^2 4) 0.23 N/mm^2 5) 0.24 N/mm^2 Mean: 0.31 N/mm^2 <u>Fracture pattern</u> Fracture pattern a: Adhesion fracture – Fracture at the interface between mortar and substrate. | Pass |

Note:

1) Testing period – 9th August 2022 to 30th September 2022.

2) *Simple Acceptance Rule is used for the conformity statement. The level of risk regarding the Probability of False Accept is up to 50% according to ILAC G8:09.



This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

TEST RESULTS:

Product : SCP Skim Top Coat
 Mix ratio : 36 % of water
 Method of Test : 1) BS EN 998-1-2016,
 Specification for mortar for masonry. Part 1: Rendering and plastering mortar
 2) BS EN 1015-18: 2002,
 Methods of test for mortar for masonry – Part 18: Determination of water absorption coefficient due to capillary action of hardened mortar

| CLAUSE | TEST METHOD/REQUIREMENT | TEST RESULTS | REMARK |
|--------------|--|---|--------|
| 5.3 5.3.1 | <p>Properties of hardened mortar General The properties relevant to the intended use and/or type of product shall be declared.</p> <p>GP: General purpose rendering/plastering mortar</p> <p>- Categories W_c 1: $C \leq 0.40 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ (for mortar intended to be used in the external elements)</p> <p>Coefficient of capillary water absorption.</p> | <p><u>Capillary water absorption</u></p> <p>1) $0.29 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ 2) $0.33 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ 3) $0.35 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ 4) $0.33 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ 5) $0.30 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ 6) $0.29 \text{ kg/m}^2 \cdot \text{min}^{0.5}$ Mean: $0.32 \text{ kg/m}^2 \cdot \text{min}^{0.5}$</p> | Pass |

Note:

1) Testing period – 9th August 2022 to 30th September 2022.

2) *Simple Acceptance Rule is used for the conformity statement. The level of risk regarding the Probability of False Accept is up to 50% according to ILAC G8:09.



| | | |
|--|--|--|
| | | |
|--|--|--|

This Test Report refers only to samples submitted by the applicant to SIRIM QAS International Sdn. Bhd. and tested by SIRIM QAS International Sdn. Bhd. This Test Report shall not be reproduced, except in full and shall not be used for any purpose by any means or forms (including but not limited to advertising purposes) without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE), SIRIM QAS International Sdn. Bhd. Please refer to the last page of this Test Report for Conditions Relating to the Use of Test Report.

CONDITIONS RELATING TO THE USE OF SIRIM QAS INTERNATIONAL TEST REPORT

1. A Test Report will be issued in respect of Testing Services conducted and shall relate only to the sample actually tested. SIRIM QAS International makes no warranty whatsoever and the Applicant shall not represent in any manner that any duplication or mass production of the Product is same as the sample actually tested or that SIRIM QAS International has tested any of the duplicated or mass-produced Product. Measurement uncertainty shall be included in the Test Report when there is no statement of conformity required. When a statement of conformity to a specification or standard is applied, the Simple Acceptance Rule is used. Unless otherwise stated, the Acceptance Rule with Guard Band is used.
2. The Test Report shall not be misused, amended, changed, varied or modified in any manner whatsoever by the Applicant or otherwise.
3. If the Test Report is to be furnished to any third party or to the public, each such Test Report shall be furnished in full, legible and in its entirety.
4. The Test Report shall not be reproduced and shall not in any event be used for any advertising purposes or whatsoever without written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE) of SIRIM QAS International of No 1, Persiaran Dato' Menteri, Building 8, Section 2, P.O. Box 7035, 40700 Shah Alam, Selangor Darul Ehsan.
5. Customer (Applicant/Manufacture/Factory, etc.) is not permitted to use any SIRIM QAS International, SIRIM or other SIRIM's subsidiaries logo or words on packaging, sample's manual, technical specification, items and products.
6. Subject to consent and written approval from the Head of Quality, Occupational Safety and Health & Environment (QOSHE) of SIRIM QAS International, the customer (Applicant/Manufacture/Factory, etc.) may use SIRIM QAS International logo or word on the promotional materials and the Applicant shall only include the phrase, "A sample of this product has been tested by SIRIM QAS International ...(Test Report No) ...(dated) ...(for what test) ...(to which standard)" or such similar words which stress that only the sample was actually tested. This phrase shall only be used for the purpose of product advertisement or product promotion (eg; brochures/flyers/official website). For avoidance of doubt, the statement shall not be used on the sample, packaging of the sample, items and products.
7. In the event there is an investigation from a Government Regulatory Agency concerning the Applicant's Test Report, SIRIM QAS International may disclose the information pertaining to the Test Report for purposes of such investigation.
8. In the event the Applicant is found in breach of this provision, SIRIM QAS International, SIRIM and/or other SIRIM's subsidiaries without prejudice to any other rights and remedies may take whatever action necessary including but not limited to:
 - a) Informing and placing a notice in the media;
 - b) Obtaining an injunction from Court (cost on a solicitor-client basis to be borne by the Applicant);
 - c) Refusing to accept any further Product for Testing Services from the Applicant or whosoever related to the Applicant, whether subsidiary or otherwise;
 - d) Instructing the Applicant to withdraw and recall the advertisement, statement or document in question and advertise a clarification and apology to SIRIM QAS International, SIRIM and/or other SIRIM's subsidiaries twice in a national publication of SIRIM QAS International's choice at the Applicant's sole cost; and
 - e) Informing or lodging a report pertaining the Applicant's Test Report with the relevant authorities.
9. SIRIM QAS International is committed in supporting an environmentally-friendly business practices by reducing paper consumption, therefore we do not issue any hard copy of Test Report to the Applicant. However, additional certified true copy(ies) or softcopy of the Test Report may be issued upon request by the Applicant upon payment of the relevant fee. The certified true copy(ies) or softcopy of test report shall only be given for test report issued not more than three (3) years from the date of issuance.
10. Issuance of Amendment Report due to the following reasons are chargeable to the Applicant :
 - a) Changes in details of the Applicant name and/or address;
 - b) Changes in details of the Manufacturer's name and/or address;
 - c) Changes in details of the Factory location name and/or address;
 - d) Changes in details of the model and/or type designation
11. However, issuance of Supplementary Report due to the following reasons are FOC :
 - a) Misprints and typo errors;
 - b) Missing technical information as agreed in PP1 form;
 - c) Test data not reported;
 - d) Mistake in reporting of test data
12. Corrections to report shall only be allowed if the date of issuance of the original report has not exceeded 6 months and shall be limited to a maximum 3 times, after either case whichever occurs earlier, an Amendment or a Supplementary Report shall not be issued.