



PRODUCT SPECIFICATION	Page :1
	Revised edition no : 00
P-736 GEAR OIL 85W-140 GL/5	Effective Date: 11-1-2024

PRODUCT DESCRIPTION

85W-140 GL/5 is a high performance gear oil formulated with premium base oil enhanced with additives possess anti-wear, pour point depression and extreme pressure properties designed to meet the requirements of gear systems.

FEATURES AND BENEFITS

- Good anti-wear protection to reduce premature wear and prolong gear life.
- Rust and corrosion protection to inhibit the rusting or corrosion of gear and bearing surfaces.

APPLICATION

- Heavy duty manual transmissions, axles and final drives, where an extreme pressure (EP) GL-5 gear oil is required.
- On-highway vehicles
- Off-highway vehicles used in various industries including construction, agriculture and forestry.
- Industrial gear sets, where an extreme pressure (EP)GL-5 gear oil is required.

PHYSICAL PROPERTIES

Property	
SAE Grade	85W-140
Specific Gravity @ 28.9°C	0.88
Viscosity @ 40°C, cst, ASTM D445	342
Viscosity @ 100°C, cst, ASTM D445	26.5
Viscosity Index, ASTM D2270	102

These data are given as an indication of typical values and not as exact specifications.

STORAGE

- Store in a dry and cool area (below 40°C).
- Keep away from direct sunlight.
- Keep away from food and children.

AVAILABLE PACKAGES

4Ltr, 18Ltr, 200Ltr

Note

All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable or his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot responsibility therefore. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property right.

No.22 & 23, Jalan Maju 1, Cemerlang Industrial Estate, 81800 Ulu Tiram, Johor, Malaysia.

Tel: 607-8675798 Fax: 607-8675799

Website: www.koyachemicals.com EMAIL: admin@koyachemicals.com