

ELTONTM

SERIES **8**

INSTANT WATER HEATER

SS808 / SP818 / SP888S



Slim / Stylish / Elegant

**SILENTS & INVERTER
TECHNOLOGY**



Silent Inverter Booster Pump

Bringing you away from noisy, crowded life style, ELTON gives you a calm experience while using SP888S instant water heater. Feel the silent technology and enjoy the moment.



Inverter Silent



Control Pressure



Energy Saving



Inverter Silent Pump Control



Silent Plus DC Inverter Pump

- LONG LASTING
- STRONGER WATER PRESSURE
- LOW NOISE SYSTEM



SP888S

Energy Saving

By using this technology, user can save up to 50% of electricity consumption. It operate in low noise and maintain the pressure up to 99%



Multi Spray Pattern HAND SHOWER

WILD



SS808

UNIQUE SLIDE BAR



Adjust to your
ideal position.



SAFE GUARD FEATURES

Built-in Double Safety ELCB System

- TEST / RESET SAFETYFUNCTION
- SURGE PROTECTION

Electronic Power Control

- INVERTER
- IDEAL TEMPERATURE



MASSAGE



ROCKET



FULL



JET



SP818



Booster Pump Control



Turbo Booster Pump

- LONG LASTING
- STRONGER WATER PRESSURE
- LOW NOISE SYSTEM



BOOSTER PUMP

“ Gives you a **DIFFERENT EXPERIENCE** of shower ”



Safety Thermostat

- ANTI SCALDING
- SAFETY THERMAL IN-OUT



Splash Proof Casing IP25

- AGAINST WATER SPLASHING
- ANTI STATIC



Incoming Pressure Control

- COUNTERBALANCE OPERATING PRESSURE
- EXTRA SECURED

Created *by Human*
Use *by Human*



Slim & Modern Body Design

Series 8 comes in an elegant slim shape with different colour design. Giving it a unique and beautiful title.



Energy Saving Technology

Energy saving up to 50% with silent inverter pump.



Safety Assurance

Well equipped with safe guard features in all model, giving user an insured guarantee on safety.



EXTRA FEATURES



1 YEAR
FULL GUARANTEE



5 YEARS WARRANTY
ON DC PUMP



SATISFY AFTER-SALES
SERVICE



SS808



SP818



SP888S

SPECIFICATION SERIES 8 (SS808, SP818, SP888S)

Power Rating	3.6kW, 240v, 50Hz
Min. Working Pressure	0.1 Bar / 1.45psi / 10 kPa
Max. Working Pressure	6.0 Bar / 87psi / 600 kPa
Min. Water Flow Rate	2.0 ℓ per minute
Max. Water Flow Rate	7.0 ℓ per minute
Piping Connection	Ø 15mm (½" BSP)
Dimension	H360 x W240 x D87 mm
Weight	SS808 - 2.9 kg SP818 - 3.8 kg SP888S - 3.5 kg



MALAYSIA



SINGAPORE



THAILAND



CANADA / USA