GET **MORE** OUT OF YOUR BIOGAS SYSTEM



The new, optimised X-UNIT generates **more energy** from the same feed, at the same time providing **greater protection** from harmful contaminants.

1C



max. Flow volume m^{3/h} 1.250*

00

MAX. SPEED CUTTING BLADE min⁻¹

MAX. DIFF. PRESSURE

* Figures apply with water as the medium

3.000

CUTS EXTREMELY WELL AND RUNS LIKE CLOCKWORK

WANGEN PUMPEN

Modular, process-optimised and very durable: the new WANGEN X-UNIT.



Low wear costs and low energy consumption optimise the efficiency of your system.

- Low energy consumption coupled with maximum substrate yield.
- **Durable, heavy-duty seal** with in-house developed cooling and lubricating function for extremely high-performance (up to 6 bar media-pressure).
- Cutting unit with rotating cutting blades speeds of up to **3,000 rpm** provide for excellent substrate digestion rates.
- Large settling tank with a large opening for the removal of foreign matter.
- Foreign matter is removed from the medium without additional energy consumption.
- The ultimate ease of servicing, thanks to rapid replacement of the cutting blade and sealing unit.
- **Galvanised components** for perfect, proven WANGEN-quality corrosion protection throughout.