



FEATURES

SPECIFICATIONS

- ▶ Up to 4K high resolution
- ▶ H.265 / H.264 video formats
- ▶ POE & DC 12V integration design
- ▶ 2.8 ~ 12mm motorized zoom lens
- ▶ Up to 50m IR range
- ▶ Dual video streams
- ▶ 80dB Wide Dynamic Range
- ▶ 3D Digital Noise Reduction
- ▶ IP66 weather-proof protection
- ▶ Support IE, Chrome, Safari, Firefox
- ▶ Latest ONVIF V2.4.1 supported
- ▶ Browser plug-in free.

Camera

Image Sensor

1/1.7" Progressive Scan CMOS

Min. Illumination

Color: 0.01 Lux @ (F2.0), B/W: 0 Lux with IR

Lens

2.8 ~ 12mm motorized zoom lens

Day & Night

IR cut filter with auto switch

DNR

3D DNR

Wide Dynamic Range

80 dB

Angle of View

TBD

Compression Standard

Video Compression

H.265 / H.264

Dual Streams

Support

Image

Max. Resolution

3840 x 2160

Frame Rate

50Hz : 25fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080)

60Hz : 30fps(3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080)

Image Setting

WDR, Compression, Rotate mode, Saturation, Brightness, Contrast

ROI Codec

Support, 4 regions

Network

Alarm Trigger

Motion detection, Network disconnect, IP address conflict

Standards

ONVIF (PROFILE S, PROFILE G), CGI, RTSP, RTMP

Interface

Communication

1 RJ45 10M / 100M Ethernet Port

On-board Storage

Build-in Micro SD/SDHC/SDXC slot, up to 128GB

Alarm Interface

1 x Alarm I/O

Audio Interface

1 x Audio In

General

Operating Conditions

Temperature : -30°C ~ 60°C (-22°F ~ 140°F) Humidity : 95% or less (Non - condensing)

Power Supply

DC12V ± 10%, POE (802.3af)

Power Consumption

Max. 8W

IR Range

Approx. 50 meters (160 feet)

Ingress Protection

IP66

Dimensions

310.2mm x 80mm x 88.3mm (12.2" x 3.1" x 3.5")

DIMENSIONS

8MP Motorized Zoom Lens Network Bullet Camera

