

UPVC SOIL, WASTE AND VENTILATING (S.W.V.) PIPES

These pipes are compiled with **MS 1063** which intended to be used for soil and waste discharge pipe work for conveyance of domestic waste water (low and high temperature), ventilating pipe work and rainwater pipe work within building structure. This standard is equivalent to **BS 5255**, **BS 4514**, **BS EN 1401** and **BS EN 1329**.



SPECIFICATIONS OF SOIL, WASTE AND VENTILATING (S.W.V.) PIPES

Colour	White
Length	4m or 6m
Type of Joint	Solvent Cement Weld Joint

NOMINAL SIZE		MEAN OUTSIDE DIAMETER (mm)		WALL THICKNESS (mm)			
				Application Area			
In.	mm	Min	Max	B		BD	
				Min	Max	Min	Max
1¼	36	36.2	36.5	3.0	3.5	-	-
1½	43	42.8	43.1	3.0	3.5	-	-
2	56	55.8	56.1	3.0	3.5	-	-
3	82	82.4	82.8	3.0	3.5	3.0	3.5
4	110	110.0	110.3	3.2	3.8	3.2	3.8
6	160	160.0	160.4	3.2	3.8	4.0	4.6
8	200	200.0	200.5	3.9	4.5	4.9	5.6
10	250	250.0	250.5	4.9	5.6	6.2	7.1
12	315	315.0	315.6	6.2	7.1	7.7	8.7

Application area code:

Code "B" = Application for components intended for use above ground inside the buildings, or for components outside buildings fixed onto the wall.
 Code "BD" = Application for components intended for above ground use for both inside the buildings, or components outside buildings fixed onto the wall and buried in building structures.

