

VigorSwitch P1280

PoE Web Smart Giga Switch



- Dual-stack IPv4/IPv6 conformity for the next generation network
- 24 x Gigabit Ethernet with additional 4 combo UTP/SFP ports for maximum connectivity
- 802.3at PoE+ with 340W budget, with schedule providing power at right time
- Support LLDP and SNMP for best management software compatibility
- Advanced QoS for application traffic prioritization
- Voice VLAN for easy VoIP devices setup and prioritize

The VigorSwitch P1280 is ideal for SOHO and small business with the high-performance capability and IPv6 management. To cater for high bandwidth traffic, it is equipped with 24 Gigabit Ethernet ports for the LAN side, and 4 combo UTP/SFP ports for the backbone side. VigorSwitch P1280 is equipped with extensive facilities for maximizing your LAN performance, VLAN capability to allow flexible network design, and QoS capability for flexible bandwidth control. Furthermore, the power saving by IEEE802.3az EEE can offer you a green Ethernet networking environment.

The VigorSwitch P1280 also offers power to all these ports with Power of Ethernet (PoE) capability. All PoE-enabled devices for the business usages, such as IP phones, wireless AP or IP Cameras can all rely on VigorSwitch P1280 switch for the power supply, you are free to position equipment wherever they should be, not being limited by the power outlet.

Virtual LAN

VLAN provides a way for businesses to assign network functions to different workgroups, branches, sections, employees or visitors, according to their operational requirements. VigorSwitch P1280 offers the Layer 2 Isolation feature (tag-based) VLAN for the groups.

The Voice VLAN function of VigorSwitch P1280 assigns a preset VLAN profile with appropriate level of QoS for VoIP traffic. This ensures that voice related traffic will not be delayed because of inappropriate priority treatment.

Bandwidth Aggregation

The Gigabit ports can be combined together to create a multi-link load-sharing trunk. Port trunks are useful for switch-to-switch cascading, providing very high full-duplex speeds.

QoS (Quality of Service)

With DrayTek VigorSwitch P1280, the QoS feature provides eight internal queues to support eight different classifications of traffic. High priority packet streams experience less delay inside the switch, which supports lower latency for certain delay-sensitive traffic. The switch classifies the packet as one of the eight priorities according to 802.1p priority tag, DiffServ and/or DSCP based. The QoS operates at full wire speed.


Energy efficiency

The VigorSwitch P1280 is fully compliant with IEEE802.3az which is an energy efficient Ethernet protocol.

The Power saving using Power Management techniques to detect the client idle and cable length automatically and provides the different power. The latest application-specific integrated circuits (ASICs), using lower-power technology, allow for lower power consumption and thinner, more efficient designs.

PoE for Efficient Installation

24-PoE ports allow power to be supplied to end devices, such as Wireless AP, IP Phones and IP cams, directly through the existing LAN cables, eliminating costs for additional AC wiring and reducing Installation Cost. It frees your wireless AP deployment from restriction due to power outlet location. PoE also comes with schedule feature to provide power in a timely manner, lowering your bill of electricity.



IP Version

- IPv4
- IPv6

Standard Compliance

- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base-T
- IEEE 802.3ab 1000Base-T
- IEEE 802.3x Flow Control Capability
- ANSI/IEEE 802.3 Auto-negotiation
- IEEE 802.1p Class of Service
- IEEE 802.1d Spanning Tree
- IEEE 802.1w Rapid Spanning Tree
- IEEE 802.3ad Port Trunk with LACP
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
- IEEE 802.1az Energy Efficient Ethernet

QoS

- Support 8 Hardware Queues
- Rate Limit
 - Port-based (Ingress/Egress)
- Queue Setting
 - WRR
 - Strict Priority
- Class of Service
 - 802.1p CoS
 - DSCP
 - CoS-DSCP
 - IP Precedence

Security

- Support Storm Control
- DoS Attack Prevention

Multicast

- Up to 256 Multicast Groups
- IGMP Snooping v2/v3 (BISS)
 - IGMP Querier
 - Immediate Leave

Link Aggregation

- Supports 8 Link Aggregation Groups with Static & LACP types
- Up to 8 Ports for Each Group
- Support Traffic Load Balancing

PoE

- PoE Mode:
 - Switch allocates sufficient power the PoE PD asked for, and dynamically distribute power to all devices.
- Status:
 - Status includes class and consumed power by Pds.
- Schedule

Diagnostics

- CPU/RAM/Port Utilization
- Event Log
- Port Mirroring
- Ping
- Port-based Cable Test

Environmental / Physical

- Power
 - Voltage: 100 ~ 240VAC
 - PoE Power Budget: 340 Watt
- Temperature
 - Operating: 0 ~ 40°C
 - Storage: -20 ~ 70°C
- Humidity
 - Operating: 10 to 90% RH (Non-condensing)
 - Storage: 5 to 90% RH (Non-condensing)
- Dimension: 45(H) x 441(W) x 270(D) mm

VLAN

- Support IEEE 802.1Q VLAN
 - Tag-based
- Protected Port
- Voice VLAN (OUI Mode)
- Management VLAN

Management

- Multiple User Account
 - Two-level Security (Admin/User)
- HTTP(s) Web User Interface
- HTTP(s)/TFTP Upgrade/Backup of
 - Firmware
 - Configuration
- Simple Network Time Protocol
- Link Layer Discovery Protocol
- Simple Network Management Protocol v1/v2c
 - MIB-II System & Interface Groups
 - Support Generic Traps
- Command Line Interface (CLI) via Telnet/SSH
- DrayTek Switch Management

Hardware Interface

- 24 x 10/100/1000Mbps Giga Ethernet with PoE+ PSE, RJ-45 (Each Port can Support Both IEEE 802.3af / 802.3at Mode)
- 4 x GbE Combo Ports, RJ45 + SFP
- 1 x Factory Reset Button

